



LNR1A334MSE Information



For Reference Only

Part Number LNR1A334MSE

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 330000UF 20% 10V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LNR1A334MSE Specifications

Manufacturer Part Number LNRIA334MSE Manufacturer Nichicon Category Capacitors Package Radial, Can - Screw Terminals Series LNR Capacitance 33000µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 15.9A @ 120Hz Ripple Current - High Frequency 18.285A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 4.055" (103.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	_	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series LNR Capacitance 330000µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Ingedance Lead Spacing 1.126" (28.60mm) Size / Dimension Lifetime (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	LNR1A334MSE
Package Radial, Can - Screw Terminals Series LNR Capacitance 330000µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.9A @ 120Hz Ripple Current - High Frequency 18.285A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 4.055" (103.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	Nichicon
PackageRadial, Can - Screw TerminalsSeriesLNRCapacitance330000µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency15.9A @ 120HzRipple Current - High Frequency18.285A @ 10kHzImpedance-Lead Spacing1.126" (28.60mm)Size / Dimension2.500" Dia (63.50mm)Height - Seated (Max)4.055" (103.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series LNR Capacitance 330000µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.9A @ 120Hz Ripple Current - High Frequency 18.285A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 4.055" (103.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 330000µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.9A @ 120Hz Ripple Current - High Frequency 18.285A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 4.055" (103.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.9A @ 120Hz Ripple Current - High Frequency 18.285A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 4.055" (103.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	LNR
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 15.9A @ 120Hz Ripple Current - High Frequency 18.285A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 4.055" (103.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Capacitance	330000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 15.9A @ 120Hz Ripple Current - High Frequency 18.285A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.9A @ 120Hz Ripple Current - High Frequency 18.285A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Voltage - Rated	10V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.9A @ 120Hz Ripple Current - High Frequency 18.285A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 4.055" (103.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 15.9A @ 120Hz Ripple Current - High Frequency 18.285A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 4.055" (103.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	5000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 18.285A @ 10kHz Impedance Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 18.285A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 4.055" (103.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 4.055" (103.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 4.055" (103.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	15.9A @ 120Hz
Lead Spacing1.126" (28.60mm)Size / Dimension2.500" Dia (63.50mm)Height - Seated (Max)4.055" (103.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	18.285A @ 10kHz
Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 4.055" (103.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.126" (28.60mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.500" Dia (63.50mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.055" (103.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

LNR1A334MSE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LNR1A334MSE Payment Methods





















LNR1A334MSE Shipping Methods













If you have any question about LNR1A334MSE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com