



### **LNRK1.12T Information**

Heisener.com

Part NumberLNRK1.12TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 1.12A 250VAC/125VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **LNRK1.12T Specifications**

Manufacturer Part NumberLNRK1.12TManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?, POWR-PRO? LLNRKFuse TypeCartridgeCurrent Rating1.12AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Report errors?		
Category  Circuit Protection Electrical, Specialty Fuses  Package  Cartridge, Non-Standard  Series  POWR-GARD?, POWR-PRO? LLNRK  Fuse Type  Cartridge  Current Rating  1.12A  Voltage Rating - AC  250V  Voltage Rating - DC  125V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Electridge, Non-Standard  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Electrical, Industrial  Features  - CE, CSA, QPL, UL  Operating Temperature  Fuse Rated Voltage  Cartridge, Non-Standard  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Electrical, Specialty Electrical  Electrical, Industrial  Features  Cartridge, Non-Standard  October Specialty Electrical  Cartridge, Non-Standard  October Specialty Electrical  Cartridge, Non-Standard  October Specialty Electrical  Electrical, Industrial  Features  Cartridge, Non-Standard  October Specialty Electrical  Cartridge, Non-Standard  October Specialty Electrical  Electrical, Industrial  Features  Cartridge, Non-Standard  October Specialty Electrical	Manufacturer Part Number	LNRK1.12T
Electrical, Specialty Fuses  Package Cartridge, Non-Standard Series POWR-GARD?, POWR-PRO? LLNRK Fuse Type Cartridge Current Rating 1.12A Voltage Rating - AC Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension  Electricale, Non-Standard South AC, 20kA DC House For Cartridge, Non-Standard Size / Dimension  Electricale, Industrial For Cartridge, Non-Standard Size / Dimension  Electricale, Non-Standard Size / Dimension  Electrica	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD?, POWR-PRO? LLNRKFuse TypeCartridgeCurrent Rating1.12AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Category	Circuit Protection
SeriesPOWR-GARD?, POWR-PRO? LLNRKFuse TypeCartridgeCurrent Rating1.12AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 1.12A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cason Cartridge Cartridge Cartridge, Non-Standard Size / Dimension Capacity (Cartridge, Non-Standard) Current Rating Sizo / Dimension Sizo / Dimension Cartridge, Non-Standard Sizo / Dimension Capacity (Cartridge, Non-Standard) Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Capacity (Cartridge, Non-Standard) Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Cartridge,	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  1.12A 1.12	Series	POWR-GARD?, POWR-PRO? LLNRK
Voltage Rating - AC  Voltage Rating - DC  125V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  250V  250V  250V  260V  125V  Response Time  Slow  Clectrical, Industrial  - CE, CSA, QPL, UL  - CE, CSA, QPL,	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  125V  126V  125V  125V	Current Rating	1.12A
Response Time  Applications  Electrical, Industrial  Features  - Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Slow  Slow  Slow  Slow  Slow  Slow  Slow  Slow  Electrical, Industrial  -  RK1  Approvals  CE, CSA, QPL, UL  - CE, CSA,	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Voltage Rating - DC	125V
Features - Class RK1  Approvals CE, CSA, QPL, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Response Time	Slow
Class RK1  Approvals CE, CSA, QPL, UL  Operating Temperature -  Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  O.563" Dia x 2.000" L (14.30mm x 50.80mm)	Class	RK1
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.563" Dia x 2.000" L (14.30mm x 50.80mm)
		Report errors?

### **LNRK1.12T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **LNRK1.12T Payment Methods**



















### **LNRK1.12T Shipping Methods**













If you have any question about LNRK1.12T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com