



LNRK225.X Information

Heisener.com

Part NumberLNRK225.XManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 225A 250VAC/125VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LNRK225.X Specifications

Manufacturer Part NumberLNRK225.XManufacturerLittelfuse Inc.CategoryCircuit ProtectionBeckageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? LLNRKFuse TypeCartridgeCurrent Rating225AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.343" Dia x 8.626" L (59.50mm x 219.10mm)Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminals Series POWR-GARD?, POWR-PRO? LLNRK Fuse Type Cartridge Current Rating 225A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals S:2.343" Dia x 8.626" L (59.50mm x 219.10mm)	Manufacturer Part Number	LNRK225.X
Beaking Capacity @ Rated Voltage Electrical, Specialty Fuses Cylindrical, Blade Terminals POWR-GARD?, POWR-PRO? LLNRK Fuse Type Cartridge Current Rating 225A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Electrical, Fuse Time Cylindrical, Blade Terminals Size / Dimension Electrical, Fuse Time Cylindrical, Blade Terminals Size / Dimension Electrical, Industrial Features - CE, CSA, QPL, UL CE, CSA, QPL, UL CE, CSA, QPL, UL CE, CSA, QPL, UL COPETATION CONTROL CONTR	Manufacturer	Littelfuse Inc.
Package Cylindrical, Blade Terminals Series POWR-GARD?, POWR-PRO? LLNRK Fuse Type Cartridge Current Rating 225A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 225A	Category	Circuit Protection
Series POWR-GARD?, POWR-PRO? LLNRK Fuse Type Cartridge Current Rating 225A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 22343" Dia x 8.626" L (59.50mm x 219.10mm)		Electrical, Specialty Fuses
Fuse Type Current Rating Current Rating 225A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Castridge Capacity @ Cartridge Capacity @ Cartridge Capacity @ Cap	Package	Cylindrical, Blade Terminals
Current Rating Current Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 225A 225A 225A 243" Dia x 8.626" L (59.50mm x 219.10mm)	Series	POWR-GARD?, POWR-PRO? LLNRK
Voltage Rating - AC Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 125V 1	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 125V 125V 125V 126V 126V 126V 126V 126V 126V 126V 126	Current Rating	225A
Response Time Applications Electrical, Industrial Features - Class RK1 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Slow Slow Slow Slow Slow Slow Slow Slow Slow Electrical, Industrial - RK1 CE, CSA, QPL, UL - CE, CSA, QPL,	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.343" Dia x 8.626" L (59.50mm x 219.10mm)	Voltage Rating - DC	125V
Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Package / Case Cylindrical, Blade Terminals Size / Dimension - 2.343" Dia x 8.626" L (59.50mm x 219.10mm)	Response Time	Slow
Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.343" Dia x 8.626" L (59.50mm x 219.10mm)	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.343" Dia x 8.626" L (59.50mm x 219.10mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.343" Dia x 8.626" L (59.50mm x 219.10mm)	Class	RK1
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.343" Dia x 8.626" L (59.50mm x 219.10mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.343" Dia x 8.626" L (59.50mm x 219.10mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 2.343" Dia x 8.626" L (59.50mm x 219.10mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 2.343" Dia x 8.626" L (59.50mm x 219.10mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	2.343" Dia x 8.626" L (59.50mm x 219.10mm)
		Report errors?

LNRK225.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LNRK225.X Payment Methods



















LNRK225.X Shipping Methods













If you have any question about LNRK225.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com