



LNT1J334MSE Information



For Reference Only

Part Number LNT1J334MSE Manufacturer Nichicon

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 330000UF 20% 63V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LNT1J334MSE Specifications

Manufacturer Part Number LNT11334MSE Manufacturer Nichicon Category Capacitors Package Radial, Can - Screw Terminals Series LNT Capacitance 330000µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency 26.1A @ 120Hz Ripple Current - High Frequency 30.015A @ 10kHz Impedance - Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) 10.000" (254.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	_	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series LNT Capacitance 330000µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 1.634 @ 120Hz Ripple Current - High Frequency 1.634 @ 10kHz Impedance Lead Spacing 1.634" (41.50mm) Size / Dimension 1.000" (254.00mm) Height - Seated (Max) 10.000" (254.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	LNT1J334MSE
Package Radial, Can - Screw Terminals Series LNT Capacitance 330000µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 26.1A @ 120Hz Ripple Current - High Frequency 30.015A @ 10kHz Impedance - Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) 10.000" (254.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	Nichicon
PackageRadial, Can - Screw TerminalsSeriesLNTCapacitance330000µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency26.1A @ 120HzRipple Current - High Frequency30.015A @ 10kHzImpedance-Lead Spacing1.634" (41.50mm)Size / Dimension3.937" Dia (100.00mm)Height - Seated (Max)10.000" (254.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series LNT Capacitance 330000µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 26.1A @ 120Hz Ripple Current - High Frequency 30.015A @ 10kHz Impedance - Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) 10.000" (254.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 330000µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 26.1A @ 120Hz Ripple Current - High Frequency 30.015A @ 10kHz Impedance - Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) 10.000" (254.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 26.1A @ 120Hz Ripple Current - High Frequency 30.015A @ 10kHz Impedance - Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) 10.000" (254.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	LNT
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 30.015A @ 10kHz Impedance - Lead Spacing 1.634" (41.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Capacitance	330000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polar Applications Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency 1.634 @ 120Hz Rippedance - Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.634" (41.50mm) Size / Dimension Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Voltage - Rated	63V
Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 30.015A @ 10kHz Impedance Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - Low Frequency Ripple Cu	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 30.015A @ 10kHz Impedance Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 30.015A @ 10kHz Impedance - Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) 10.000" (254.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) 10.000" (254.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance - Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) 10.000" (254.00mm) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	26.1A @ 120Hz
Lead Spacing1.634" (41.50mm)Size / Dimension3.937" Dia (100.00mm)Height - Seated (Max)10.000" (254.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	30.015A @ 10kHz
Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) 10.000" (254.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.634" (41.50mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.937" Dia (100.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	10.000" (254.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

LNT1J334MSE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LNT1J334MSE Payment Methods



















LNT1J334MSE Shipping Methods













If you have any question about LNT1J334MSE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com