



LNT1K683MSE Information



For Reference Only

Part Number LNT1K683MSE

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 68000UF 20% 80V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LNT1K683MSE Specifications

Manufacturer Part Number LNT1K683MSE Manufacturer Nichicon Category Capacitors Package Radial, Can - Screw Terminals Series LNT Capacitance 68000µF Tolerance ±20% Voltage - Rated 80V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17A @ 120Hz Ripple Current - High Frequency 19.55A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 5.630" (143.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	_	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Scries LNT Capacitance 68000µF Tolerance ±20% Voltage - Rated 80V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Inpedance Lead Spacing 1.252" (31.80mm) Size / Dimension Light - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	LNT1K683MSE
Package Radial, Can - Screw Terminals Series LNT Capacitance 68000µF Tolerance ±20% Voltage - Rated 80V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17A @ 120Hz Ripple Current - High Frequency 19.55A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 5.630" (143.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	Nichicon
PackageRadial, Can - Screw TerminalsSeriesLNTCapacitance68000μFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17A @ 120HzRipple Current - High Frequency19.55A @ 10kHzImpedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)5.630" (143.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series LNT Capacitance 68000µF Tolerance ±20% Voltage - Rated 80V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17A @ 120Hz Ripple Current - High Frequency 19.55A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 5.630" (143.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance68000μFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17A @ 120HzRipple Current - High Frequency19.55A @ 10kHzImpedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)5.630" (143.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 80V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17A @ 120Hz Ripple Current - High Frequency 19.55A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 5.630" (143.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	LNT
Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17A @ 120HzRipple Current - High Frequency19.55A @ 10kHzImpedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)5.630" (143.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	68000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 17A @ 120Hz Ripple Current - High Frequency 19.55A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 5.630" (143.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17A @ 120Hz Ripple Current - High Frequency 19.55A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Voltage - Rated	80V
Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 19.55A @ 10kHz Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency 17A @ 120Hz Ripple Current - High Frequency 19.55A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 19.55A @ 10kHz Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 19.55A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 5.630" (143.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 5.630" (143.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 5.630" (143.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	17A @ 120Hz
Lead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)5.630" (143.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	19.55A @ 10kHz
Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 5.630" (143.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.252" (31.80mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.543" Dia (90.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	5.630" (143.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

LNT1K683MSE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LNT1K683MSE Payment Methods



















LNT1K683MSE Shipping Methods













If you have any question about LNT1K683MSE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com