



### **LNT2C472MSE Information**



For Reference Only

Part Number LNT2C472MSE

Manufacturer Nichicon
Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 4700UF 20% 160V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **LNT2C472MSE Specifications**

Manufacturer Part Number         LNT2C472MSE           Manufacturer         Nichicon           Category         Capacitors           Package         Radial, Can - Screw Terminals           Scries         LNT           Capacitance         4700µF           Tolerance         ±20%           Voltage - Rated         160V           ESR (Equivalent Scries Resistance)         -           ESR (Equivalent Scries Resistance)         -           Operating Temperature         2000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         General Purpose           Ripple Current - Low Frequency         4.5A @ 120Hz           Ripple Current - High Frequency         6.75A @ 10kHz           Impedance         -           Lead Spacing         0.866" (22.00mm)           Size / Dimension         2.008" Dia (51.00mm)           Height - Seated (Max)         4.055" (103.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	•	
CategoryCapacitorsPackageRadial, Can - Screw TerminalsSeriesLNTCapacitance4700µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.5A @ 120HzRipple Current - High Frequency6.75A @ 10kHzImpedance-Lead Spacing0.866" (22.00mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.055" (103.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer Part Number	LNT2C472MSE
Package         Radial, Can - Screw Terminals           Series         LNT           Capacitance         4700μF           Tolerance         ±20%           Voltage - Rated         160V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         4.5A @ 120Hz           Ripple Current - High Frequency         6.75A @ 10kHz           Impedance         -           Lead Spacing         0.866" (22.00mm)           Size / Dimension         2.008" Dia (51.00mm)           Height - Seated (Max)         4.055" (103.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Manufacturer	Nichicon
Package         Radial, Can - Screw Terminals           Series         LNT           Capacitance         4700µF           Tolerance         ±20%           Voltage - Rated         160V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         4.5A @ 120Hz           Ripple Current - High Frequency         6.75A @ 10kHz           Impedance         -           Lead Spacing         0.866" (22.00mm)           Size / Dimension         2.008" Dia (51.00mm)           Height - Seated (Max)         4.055" (103.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Category	Capacitors
Series         LNT           Capacitance         4700μF           Tolerance         ±20%           Voltage - Rated         160V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         4.5A @ 120Hz           Ripple Current - High Frequency         6.75A @ 10kHz           Impedance         -           Lead Spacing         0.866" (22.00mm)           Size / Dimension         2.008" Dia (51.00mm)           Height - Seated (Max)         4.055" (103.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance         4700µF           Tolerance         ±20%           Voltage - Rated         160V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         4.5A @ 120Hz           Ripple Current - High Frequency         6.75A @ 10kHz           Impedance         -           Lead Spacing         0.866" (22.00mm)           Size / Dimension         2.008" Dia (51.00mm)           Height - Seated (Max)         4.055" (103.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 160V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C  Operating Temperature -25°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 4.5A @ 120Hz  Ripple Current - High Frequency 6.75A @ 10kHz  Impedance - Lead Spacing 0.866" (22.00mm)  Size / Dimension 2.008" Dia (51.00mm)  Height - Seated (Max) 4.055" (103.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Raistance) -  Raidal, Can - Screw Terminals	Series	LNT
Voltage - Rated160 VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.5A @ 120HzRipple Current - High Frequency6.75A @ 10kHzImpedance-Lead Spacing0.866" (22.00mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.055" (103.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	4700μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -25°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  4.5A @ 120Hz  Ripple Current - High Frequency  6.75A @ 10kHz  Impedance  - Lead Spacing  0.866" (22.00mm)  Size / Dimension  4.055" (103.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -25°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  4.5A @ 120Hz  Ripple Current - High Frequency  6.75A @ 10kHz  Impedance  Lead Spacing  0.866" (22.00mm)  Size / Dimension  4.055" (103.00mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Voltage - Rated	160V
Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.5A @ 120Hz Ripple Current - High Frequency 6.75A @ 10kHz Impedance - Lead Spacing 0.866" (22.00mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 4.055" (103.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency A.5A @ 120Hz Ripple Current - High Frequency 6.75A @ 10kHz Impedance - Lead Spacing 0.866" (22.00mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 4.055" (103.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 4.5A @ 120Hz Ripple Current - High Frequency 6.75A @ 10kHz Impedance - Lead Spacing 0.866" (22.00mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 4.055" (103.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  6.75A @ 10kHz  Impedance  - Lead Spacing  0.866" (22.00mm)  Size / Dimension  2.008" Dia (51.00mm)  Height - Seated (Max)  4.055" (103.00mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency  Impedance  Lead Spacing  0.866" (22.00mm)  Size / Dimension  2.008" Dia (51.00mm)  Height - Seated (Max)  4.055" (103.00mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Applications	General Purpose
Impedance-Lead Spacing0.866" (22.00mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.055" (103.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	4.5A @ 120Hz
Lead Spacing0.866" (22.00mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.055" (103.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	6.75A @ 10kHz
Size / Dimension 2.008" Dia (51.00mm)  Height - Seated (Max) 4.055" (103.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Lead Spacing	0.866" (22.00mm)
Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.008" Dia (51.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.055" (103.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

#### **LNT2C472MSE Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **LNT2C472MSE Payment Methods**



















## **LNT2C472MSE Shipping Methods**













If you have any question about LNT2C472MSE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com