



#### **LNT2C683MSE Information**



For Reference Only

Part Number LNT2C683MSE

Manufacturer Nichicon
Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 68000UF 20% 160V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **LNT2C683MSE Specifications**

Manufacturer Part Number         LNT2C683MSE           Manufacturer         Nichicon           Category         Capacitors           Package         Radial, Can - Screw Terminals           Series         LNT           Capacitance         6800µF           Tolerance         ±20%           Voltage - Rated         160V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         General Purpose           Ripple Current - Low Frequency         19.2A @ 120Hz           Ripple Current - High Frequency         23.04A @ 10kHz           Impedance         -           Lead Spacing         1.634" (41.50mm)           Size / Dimension         3.937" Dia (100.00mm)           Height - Seated (Max)         10.000" (254.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	*	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series LNT Capacitance 68000µF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 19.2A @ 120Hz Ripple Current - High Frequency Lead Spacing 1.634" (41.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	LNT2C683MSE
Aluminum Electrolytic Capacitors  Package Radial, Can - Screw Terminals  Series LNT  Capacitance 68000µF  Tolerance ±20%  Voltage - Rated 160V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C  Operating Temperature -25°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 19.2A @ 120Hz  Ripple Current - High Frequency 23.04A @ 10kHz  Impedance - Lead Spacing 1.634" (41.50mm)  Size / Dimension 3.937" Dia (100.00mm)  Height - Seated (Max) 10.000" (254.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Manufacturer	Nichicon
PackageRadial, Can - Screw TerminalsSeriesLNTCapacitance68000μFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19.2A @ 120HzRipple Current - High Frequency23.04A @ 10kHzImpedance-Lead Spacing1.634" (41.50mm)Size / Dimension3.937" Dia (100.00mm)Height - Seated (Max)10.000" (254.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series         LNT           Capacitance         68000µF           Tolerance         ±20%           Voltage - Rated         160V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         19.2A @ 120Hz           Ripple Current - High Frequency         23.04A @ 10kHz           Impedance         -           Lead Spacing         1.634" (41.50mm)           Size / Dimension         3.937" Dia (100.00mm)           Height - Seated (Max)         10.000" (254.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance         68000μF           Tolerance         ±20%           Voltage - Rated         160V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         19.2A @ 120Hz           Ripple Current - High Frequency         23.04A @ 10kHz           Impedance         -           Lead Spacing         1.634" (41.50mm)           Size / Dimension         3.937" Dia (100.00mm)           Height - Seated (Max)         10.000" (254.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 160V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C  Operating Temperature -25°C ~ 105°C  Polarization Polar  Applications General Purpose Ripple Current - Low Frequency 19.2A @ 120Hz Ripple Current - High Frequency 23.04A @ 10kHz  Impedance - Lead Spacing 1.634" (41.50mm)  Size / Dimension 3.937" Dia (100.00mm)  Height - Seated (Max) 10.000" (254.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Series	LNT
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -25°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  19.2A @ 120Hz  Ripple Current - High Frequency  23.04A @ 10kHz  Impedance  -  Lead Spacing  1.634" (41.50mm)  Size / Dimension  3.937" Dia (100.00mm)  Height - Seated (Max)  10.000" (254.00mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Capacitance	68000μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -25°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  19.2A @ 120Hz  Ripple Current - High Frequency  23.04A @ 10kHz  Impedance  - Lead Spacing  1.634" (41.50mm)  Size / Dimension  3.937" Dia (100.00mm)  Height - Seated (Max)  10.000" (254.00mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -25°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  19.2A @ 120Hz  Ripple Current - High Frequency  23.04A @ 10kHz  Impedance  - Lead Spacing  1.634" (41.50mm)  Size / Dimension  3.937" Dia (100.00mm)  Height - Seated (Max)  10.000" (254.00mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Voltage - Rated	160V
Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 19.2A @ 120Hz Ripple Current - High Frequency 23.04A @ 10kHz Impedance - Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) 10.000" (254.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - Low Frequency Ripple C	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 19.2A @ 120Hz Ripple Current - High Frequency 23.04A @ 10kHz Impedance - Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) 10.000" (254.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  23.04A @ 10kHz  Impedance  - Lead Spacing  1.634" (41.50mm)  Size / Dimension  3.937" Dia (100.00mm)  Height - Seated (Max)  10.000" (254.00mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency  Impedance - Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) 10.000" (254.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance - Lead Spacing 1.634" (41.50mm) Size / Dimension 3.937" Dia (100.00mm) Height - Seated (Max) 10.000" (254.00mm) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	19.2A @ 120Hz
Lead Spacing1.634" (41.50mm)Size / Dimension3.937" Dia (100.00mm)Height - Seated (Max)10.000" (254.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	23.04A @ 10kHz
Size / Dimension 3.937" Dia (100.00mm)  Height - Seated (Max) 10.000" (254.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Lead Spacing	1.634" (41.50mm)
Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.937" Dia (100.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	10.000" (254.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

#### **LNT2C683MSE Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **LNT2C683MSE Payment Methods**



















## **LNT2C683MSE Shipping Methods**













If you have any question about LNT2C683MSE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com