



### **LNT2V822MSEJ Information**



For Reference Only

Part Number LNT2V822MSEJ

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 8200UF 20% 350V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **LNT2V822MSEJ Specifications**

Manufacturer Part Number         LNT2V822MSEJ           Manufacturer         Nichicon           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Screw Terminals           Series         LNT           Capacitance         \$200µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           ESR (Equivalent Series Resistance)         -           Uifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         29.3A @ 120Hz           Ripple Current - High Frequency         41.02A @ 10kHz           Impedance         -           Lead Spacing         1.252" (31.80mm)           Size / Dimension         3.543" Dia (90.00mm)           Height - Seated (Max)         6.024" (153.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Scries LNT Capacitance 8200µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Scries Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 41.02A @ 10kHz Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	LNT2V822MSEJ
Package         Radial, Can - Screw Terminals           Series         LNT           Capacitance         8200μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         29.3A @ 120Hz           Ripple Current - High Frequency         41.02A @ 10kHz           Impedance         -           Lead Spacing         1.252" (31.80mm)           Size / Dimension         3.543" Dia (90.00mm)           Height - Seated (Max)         6.024" (153.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Manufacturer	Nichicon
Package Radial, Can - Screw Terminals  Series LNT  Capacitance 8200µF  Tolerance ±20%  Voltage - Rated 350V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C  Operating Temperature -25°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 29.3A @ 120Hz  Ripple Current - High Frequency 41.02A @ 10kHz  Impedance - Lead Spacing 1.252" (31.80mm)  Size / Dimension 3.543" Dia (90.00mm)  Height - Seated (Max) 6.024" (153.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Category	Capacitors
Series         LNT           Capacitance         8200µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         29.3A @ 120Hz           Ripple Current - High Frequency         41.02A @ 10kHz           Impedance         -           Lead Spacing         1.252" (31.80mm)           Size / Dimension         3.543" Dia (90.00mm)           Height - Seated (Max)         6.024" (153.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance       8200μF         Tolerance       ±20%         Voltage - Rated       350V         ESR (Equivalent Series Resistance)       -         Lifetime @ Temp.       5000 Hrs @ 105°C         Operating Temperature       -25°C ~ 105°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       29.3A @ 120Hz         Ripple Current - High Frequency       41.02A @ 10kHz         Impedance       -         Lead Spacing       1.252" (31.80mm)         Size / Dimension       3.543" Dia (90.00mm)         Height - Seated (Max)       6.024" (153.00mm)         Surface Mount Land Size       -         Mounting Type       Chassis Mount         Package / Case       Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 350V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C  Operating Temperature -25°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 29.3A @ 120Hz  Ripple Current - High Frequency 41.02A @ 10kHz  Impedance - Lead Spacing 1.252" (31.80mm)  Size / Dimension 3.543" Dia (90.00mm)  Height - Seated (Max) 6.024" (153.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Series	LNT
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  5000 Hrs @ 105°C  Operating Temperature  -25°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  41.02A @ 10kHz  Impedance  -  Lead Spacing  1.252" (31.80mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Roon Hrs @ 105°C  -25°C ~ 105°	Capacitance	8200µF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  5000 Hrs @ 105°C  Operating Temperature  -25°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  29.3A @ 120Hz  Ripple Current - High Frequency  41.02A @ 10kHz  Impedance  -  Lead Spacing  1.252" (31.80mm)  Size / Dimension  3.543" Dia (90.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -25°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  41.02A @ 120Hz  Impedance  Lead Spacing  1.252" (31.80mm)  Size / Dimension  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  5000 Hrs @ 105°C  Consorted  -25°C ~ 105°C  General Purpose  41.02A @ 120Hz  41.02A @ 10kHz  -  6.024" (153.00mm)  Chassis Mount  Radial, Can - Screw Terminals	Voltage - Rated	350V
Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 29.3A @ 120Hz Ripple Current - High Frequency 41.02A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 29.3A @ 120Hz  Ripple Current - High Frequency 41.02A @ 10kHz  Impedance -  Lead Spacing 1.252" (31.80mm)  Size / Dimension 3.543" Dia (90.00mm)  Height - Seated (Max) 6.024" (153.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 29.3A @ 120Hz Ripple Current - High Frequency 41.02A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 6.024" (153.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  41.02A @ 10kHz  Impedance  - Lead Spacing  1.252" (31.80mm)  Size / Dimension  3.543" Dia (90.00mm)  Height - Seated (Max)  6.024" (153.00mm)  Surface Mount Land Size  - Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency  41.02A @ 10kHz  Impedance  -  Lead Spacing  1.252" (31.80mm)  Size / Dimension  3.543" Dia (90.00mm)  Height - Seated (Max)  6.024" (153.00mm)  Surface Mount Land Size  -  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Applications	General Purpose
Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 6.024" (153.00mm) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	29.3A @ 120Hz
Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 6.024" (153.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	41.02A @ 10kHz
Size / Dimension 3.543" Dia (90.00mm)  Height - Seated (Max) 6.024" (153.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Lead Spacing	1.252" (31.80mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.543" Dia (90.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	6.024" (153.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

#### **LNT2V822MSEJ Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **LNT2V822MSEJ Payment Methods**





















### **LNT2V822MSEJ Shipping Methods**













If you have any question about LNT2V822MSEJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com