



LNX2L682MSEJ Information



For Reference Only

Part Number LNX2L682MSEJ

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 6800UF 20% 550V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LNX2L682MSEJ Specifications

Manufacturer Part Number LNX2L682MSEJ Manufacturer Nichicon Category Capacitors Package Aduminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series LNX Capacitance 6800µF Tolerance ±20% Voltage - Rated 550V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 19.5A @ 120Hz Ripple Current - High Frequency - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.780" (223.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
CategoryCapacitorsPackageRadial, Can - Screw TerminalsScriesLNXCapacitance6800µFTolerance±20%Voltage - Rated550VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19.5A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)8.780" (223.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer Part Number	LNX2L682MSEJ
PackageRadial, Can - Screw TerminalsSeriesLNXCapacitance6800μFTolerance±20%Voltage - Rated550VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19.5A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)8.780" (223.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer	Nichicon
PackageRadial, Can - Screw TerminalsSeriesLNXCapacitance6800µFTolerance±20%Voltage - Rated550VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19.5A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)8.780" (223.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series LNX Capacitance 6800µF Tolerance ±20% Voltage - Rated 550V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 19.5A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.780" (223.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 6800µF Tolerance ±20% Voltage - Rated 550V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 19.5A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.780" (223.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 550V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 19.5A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.780" (223.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Raisean Associated Associate	Series	LNX
Voltage - Rated550VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19.5A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)8.780" (223.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	6800μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 19.5A @ 120Hz Ripple Current - High Frequency Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.780" (223.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 5000 Hrs @ 85°C -25°C ~ 85°C Polar -25°C ~ 85°C -25°C ~ 85°C -210Hz -210H	Voltage - Rated	550V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 19.5A @ 120Hz Ripple Current - High Frequency - Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 19.5A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.780" (223.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	5000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Ripple Current - Low Frequency 19.5A @ 120Hz 19.5A @ 120Hz 1.252" (31.80mm) 1.252" (31.80mm) 8.780" (223.00mm) 8.780" (223.00mm) Chassis Mount Radial, Can - Screw Terminals	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.780" (223.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)8.780" (223.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	19.5A @ 120Hz
Lead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)8.780" (223.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.780" (223.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.252" (31.80mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.543" Dia (90.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	8.780" (223.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

LNX2L682MSEJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LNX2L682MSEJ Payment Methods



















LNX2L682MSEJ Shipping Methods













If you have any question about LNX2L682MSEJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com