



LNY2W332MSEF Information



For Reference Only

Part Number LNY2W332MSEF

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 3300UF 20% 450V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LNY2W332MSEF Specifications

Manufacturer Part Number Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals LNY Capacitance Tolerance Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications Ripple Current - Low Frequency Linch Capacitors Radial, Can - Screw Terminals LNY - Screw Terminals - LNY - Screw Terminals - S
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesLNYCapacitance3300μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral Purpose
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
PackageRadial, Can - Screw TerminalsSeriesLNYCapacitance $3300μF$ Tolerance $±20%$ Voltage - Rated $450V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $2000 Hrs @ 85°C$ Operating Temperature $-40°C \sim 85°C$ PolarizationPolarApplicationsGeneral Purpose
SeriesLNYCapacitance $3300μF$ Tolerance $\pm 20\%$ Voltage - Rated $450V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $2000 Hrs @ 85°C$ Operating Temperature $-40°C \sim 85°C$ PolarizationPolarApplicationsGeneral Purpose
Capacitance $3300μF$ Tolerance $\pm 20\%$ Voltage - Rated $450V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $2000 \text{ Hrs } @ 85°C$ Operating Temperature $-40°C \sim 85°C$ PolarizationPolarApplicationsGeneral Purpose
Tolerance $\pm 20\%$ Voltage - Rated $\pm 50\%$ ESR (Equivalent Series Resistance) - Lifetime @ Temp. $\pm 2000 \text{ Hrs } @ 85\%$ Operating Temperature $\pm 40\%$ $\pm 40\%$ $\pm 40\%$ Polarization Polar Applications General Purpose
Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose
Lifetime @ Temp. $2000 \text{Hrs} @ 85^{\circ} \text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose
Polarization Polar Applications General Purpose
Applications General Purpose
Ripple Current - Low Frequency 11.1A @ 120Hz
Ripple Current - High Frequency 15.54A @ 10kHz
Impedance -
Lead Spacing 0.866" (22.00mm)
Size / Dimension 2.008" Dia (51.00mm)
Height - Seated (Max) 6.693" (170.00mm)
Surface Mount Land Size -
Mounting Type Chassis Mount
Package / Case Radial, Can - Screw Terminals
Report errors

LNY2W332MSEF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LNY2W332MSEF Payment Methods



















LNY2W332MSEF Shipping Methods













If you have any question about LNY2W332MSEF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com