

LP120-100B20 Information

Heisener.com

Part Number LP120-100B20

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR SEMI-TORO 12VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LP120-100B20 Specifications

Manufacturer LP120-100B20 Manufacturer Pulse Electronics Power Category Transformers Power Transformers Power Transformers Series Low Profile Plug-In Type Semi-Toroidal Voltage - Primary - Voltage - Secondary (Full Load) Parallel 60V, Series 120V Current - Output (Max) Parallel 200mA, Series 100mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) 27.05mm Voltage - Isolation 1500Vrms Weight 0.688 lb (312.07g)		
Category Transformers Power Transformers Package - Series Low Profile Plug-In Type Semi-Toroidal Voltage - Primary - Voltage - Secondary (Full Load) Parallel 60V, Series 120V Current - Output (Max) Parallel 200mA, Series 100mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) 27.05mm Voltage - Isolation 1500Vrms Weight 0.688 lb (312.07g)	Manufacturer Part Number	LP120-100B20
Package - Series Low Profile Plug-In Type Semi-Toroidal Voltage - Primary - Voltage - Secondary (Full Load) Parallel 60V, Series 120V Current - Output (Max) Parallel 200mA, Series 100mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) 27.05mm Voltage - Isolation 1500Vrms Weight 0.688 lb (312.07g)	Manufacturer	Pulse Electronics Power
Package - Series Low Profile Plug-In Type Semi-Toroidal Voltage - Primary - Voltage - Secondary (Full Load) Parallel 60V, Series 120V Current - Output (Max) Parallel 200mA, Series 100mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) 27.05mm Voltage - Isolation 1500Vrms Weight 0.688 lb (312.07g)	Category	Transformers
SeriesLow Profile Plug-InTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 200mA, Series 100mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)27.05mmVoltage - Isolation1500VrmsWeight0.688 lb (312.07g)		Power Transformers
Type Semi-Toroidal Voltage - Primary - Voltage - Secondary (Full Load) Parallel 60V, Series 120V Current - Output (Max) Parallel 200mA, Series 100mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) 27.05mm Voltage - Isolation 1500Vrms Weight 0.688 lb (312.07g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 60V, Series 120V Current - Output (Max) Parallel 200mA, Series 100mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) Voltage - Isolation Weight P. Geries 120V Parallel 60V, Series 120V Parallel 200mA, Series 100mA Parallel 200mA, Series 100mA Parallel 200mA, Series 100mA Parallel 200mA, Series 100mA Parallel 60V, Series 120V Parallel 200mA, Series 100mA Dual Secondary Winding(s) Dual Secondary Winding(s) Dual Center Tap No 12 VA 15 VA 16 VA 17 VA 17 VA 18 VA 18 VA 19 VA 19 VA 10 VA 10 VA 10 VA 10 VA 10 VA 11 VA 11 VA 11 VA 11 VA 12 VA 13 VA 14 VA 15 VA 15 VA 16 VA 17 VA 17 VA 18 VA 18 VA 18 VA 19 VA 10 VA 1	Series	Low Profile Plug-In
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 200mA, Series 100mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 60V, Series 120V Parallel 200mA, Series 100mA Parallel 200mA, Series 120V Parallel 200mA, Series 120V Parallel 200mA Parallel 200mA, Series 120V Parallel 200mA Parallel 60V, Series 120V Parallel 60V, Series 120V Parallel 200mA Parallel 2	Туре	Semi-Toroidal Semi-Toroidal
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) Voltage - Isolation Parallel 200mA, Series 100mA Dual Pull No Powal Po No Powal Po No Po	Voltage - Primary	-
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight Dual No 2000 No 12 VA Through Hole 1500Vrms 0.688 lb (312.07g)	Voltage - Secondary (Full Load)	Parallel 60V, Series 120V
Secondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)27.05mmVoltage - Isolation1500VrmsWeight0.688 lb (312.07g)	Current - Output (Max)	Parallel 200mA, Series 100mA
Center TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)27.05mmVoltage - Isolation1500VrmsWeight0.688 lb (312.07g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.688 lb (312.07g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) 27.05mm Voltage - Isolation 1500Vrms Weight 0.688 lb (312.07g)	Center Tap	No
Termination Style PC Pin Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) 27.05mm Voltage - Isolation 1500Vrms Weight 0.688 lb (312.07g)	Power - Max	12 VA
Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) 27.05mm Voltage - Isolation 1500Vrms Weight 0.688 lb (312.07g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.688 lb (312.07g)	Termination Style	PC Pin
Voltage - Isolation 1500Vrms Weight 0.688 lb (312.07g)	Size / Dimension	63.50mm L x 50.80mm W
Weight 0.688 lb (312.07g)	Height - Seated (Max)	27.05mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	0.688 lb (312.07g)
		Report errors?

LP120-100B20 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LP120-100B20 Payment Methods





















LP120-100B20 Shipping Methods













If you have any question about LP120-100B20, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com