

LP20-300B7

equest a Quote

LP20-300B7 Information

| Heisener.com | Part Number | LP20-300B7 | |
|--------------------|--------------|---|---|
| | Manufacturer | Pulse Electronics Power | Γ |
| | Category | Transformers Power Transformers | Ē |
| | Description | XFRMR SEMI-TORO 6VA THRU HOLE | |
| | Package | - | |
| | | For the pricing/inventory/lead time, please contact | L |
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LP20-300B7 Specifications

| Manufacturer Part NumberLP20-300B7Manufacturer QPulse Electronics PowerCategoryTransformersPackage-SeriesLow Profile Plug-InTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 600mA, Series 300mAPower - MaxOualConter TapNoPower - Max6 VAMounting TypeThrough HoleSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)21.59mmVoltage - Isolation1500Yrms | | |
|--|---------------------------------|------------------------------|
| Category Transformers Power Transformers Package - Series Low Profile Plug-In Type Semi-Toroidal Voltage - Primary Semi-Toroidal Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 600mA, Series 300mA Secondary Winding(s) Dual Secondary Winding(s) Dual Power - Max 6 VA Nounting Type Prinary Minding Support Size / Dimension Proly Hole Ster (Max) Secondary Winding Support Power - Max Secondary Support Nounting Type Secondary Support Power - Max Secondary Support Ster / Dimension | Manufacturer Part Number | LP20-300B7 |
| Power TransformersPackage-SeriesLow Profile Plug-InTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 600mA, Series 300mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleSize / Dimension21.59mmHeight - Seated (Max)510VrmsVoltage - Isolation500VrmsWeight0.438 lb (198.67g) | Manufacturer | Pulse Electronics Power |
| Package-SeriesLow Profile Plug-InTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Prallel 10V, Series 20VCurrent - Output (Max)Parallel 600mA, Series 300mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleSter JD ImensionPrinage HoleSter JD Imension1.50mm La 39.67mm WVoltage - Isolation1.500mmsWith Seated (Max)1.500mmsWeight0.438 b (198.67g) | Category | Transformers |
| SeriesLow Profile Plug-InTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 600mA, Series 300mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension1.59mmHeight - Seated (Max)1.50VrmsWottge - Isolation500VrmsWeight0.438 lb (198.67g) | | Power Transformers |
| TypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 600mA, Series 300mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WVoltage - Isolation1500VrmsWeight0.438 lb (198.67g) | Package | - |
| Yoltage - Primary-Voltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 600mA, Series 300mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension21.59mmHeight - Seated (Max)1500VrmsWoitge - Isolation0.438 lb (198.67g) | Series | Low Profile Plug-In |
| Voltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 600mA, Series 300mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)1500VrmsVoltage - Isolation0.438 lb (198.67g) | Туре | Semi-Toroidal |
| Current - Output (Max)Parallel 600mA, Series 300mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)1500VrmsVoltage - Isolation0.438 lb (198.67g) | Voltage - Primary | - |
| Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)21.59mmVoltage - Isolation1500VrmsWeight0.438 lb (198.67g) | Voltage - Secondary (Full Load) | Parallel 10V, Series 20V |
| Secondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)1500VrmsVoltage - Isolation1500VrmsWeight0.438 lb (198.67g) | Current - Output (Max) | Parallel 600mA, Series 300mA |
| Center TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)21.59mmVoltage - Isolation1500VrmsWeight0.438 lb (198.67g) | Primary Winding(s) | Dual |
| Power - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)21.59mmVoltage - Isolation1500VrmsWeight0.438 lb (198.67g) | Secondary Winding(s) | Dual |
| Mounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)21.59mmVoltage - Isolation1500VrmsWeight0.438 lb (198.67g) | Center Tap | No |
| Termination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)21.59mmVoltage - Isolation1500VrmsWeight0.438 lb (198.67g) | Power - Max | 6 VA |
| Size / Dimension 47.63mm L x 39.67mm W Height - Seated (Max) 21.59mm Voltage - Isolation 1500Vrms Weight 0.438 lb (198.67g) | Mounting Type | Through Hole |
| Height - Seated (Max)21.59mmVoltage - Isolation1500VrmsWeight0.438 lb (198.67g) | Termination Style | PC Pin |
| Voltage - Isolation 1500Vrms Weight 0.438 lb (198.67g) | Size / Dimension | 47.63mm L x 39.67mm W |
| Weight 0.438 lb (198.67g) | Height - Seated (Max) | 21.59mm |
| | Voltage - Isolation | 1500Vrms |
| Report errors? | Weight | 0.438 lb (198.67g) |
| | | Report errors? |

LP20-300B7 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about LP20-300B7, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com