

LP24-500B10

LP24-500B10 Information

Heisener.com	Part Number Manufacturer Category Description Package	LP24-500B10 Pulse Electronics Power Transformers Power Transformers XFRMR SEMI-TORO 12VA THRU HOLE - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LP24-500B10 Specifications

ManufacturerPulse Electronics PowerCategoryTransformersPackagePower TransformersPackage-SeriesLow Profile Plug-InTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)DualPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleSize / Dimension63.50mm L x 50.80mm WBight - Seated (Max)500Vrms		
CategoryTransformersPackage-Package-SeriesLow Profile Plug-InTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 1A, Series 500mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAPower - MaxSecondary I PlugSize / DimensionScomm L x 50.80mm WSize / DimensionScomm L x 50.80mm WHeight - Seated (Max)ScowrmsWeightScowrmsWeightScowrmsWeightScowrmsWeightScowrmsWeightScowrmsWeightScowrmsWeightScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsScowrmsStowrmsSco	Manufacturer Part Number	LP24-500B10
ParkagePower TransformersPackage-SeriesLow Profile Plug-InTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 1A, Series 500mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)27.05mmWoltage - Isolation1500VrmsWeight0.688 lb (312.07g)	Manufacturer	Pulse Electronics Power
Package-SeriesLow Profile Plug-InStreisSemi-ToroidalTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 1A, Series 500mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StyleSecondary Minding(s)Size / Dimension63.50mm L x 50.80mm WNotage - Isolation50.0VrmsWeightSecondary Minding(s)	Category	Transformers
SeriesLow Profile Plug-InTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 1A, Series 500mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StyleSecondary Minding(s)Size / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)1500VrmsWeightNo		Power Transformers
TypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 1A, Series 500mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination Style63.50mm L x 50.80mm WSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)1500VrmsWeight0.688 lb (312.07g)	Package	-
PrimaryFinal ControlVoltage - Primary-Voltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 1A, Series 500mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination Style63.50mm L x 50.80mm WSize / Dimension1500VrmsWeight0.688 lb (312.07g)	Series	Low Profile Plug-In
Voltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 1A, Series 500mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleFermination Style9C PinSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)27.05mmWoltage - Isolation1500VrmsWeight0.688 lb (312.07g)	Туре	Semi-Toroidal
Current - Output (Max)Parallel 1A, Series 500mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleFermination StylePC PinSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)27.05mmVoltage - Isolation1500VrmsWeight0.688 lb (312.07g)	Voltage - Primary	-
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)27.05mmVoltage - Isolation1500VrmsWeight0.688 lb (312.07g)	Voltage - Secondary (Full Load)	Parallel 12V, Series 24V
Secondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleFermination Style9C PinSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)27.05mmVoltage - Isolation1500VrmsWeight0.688 lb (312.07g)	Current - Output (Max)	Parallel 1A, Series 500mA
Center TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)27.05mmVoltage - Isolation1500VrmsWeight0.688 lb (312.07g)	Primary Winding(s)	Dual
Power - Max12 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)27.05mmVoltage - Isolation1500VrmsWeight0.688 lb (312.07g)	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)27.05mmVoltage - Isolation1500VrmsWeight0.688 lb (312.07g)	Center Tap	No
Termination StylePC PinSize / Dimension63.50mm L x 50.80mm WHeight - Seated (Max)27.05mmVoltage - Isolation1500VrmsWeight0.688 lb (312.07g)	Power - Max	12 VA
Size / Dimension 63.50mm L x 50.80mm W Height - Seated (Max) 27.05mm Voltage - Isolation 1500Vrms Weight 0.688 lb (312.07g)	Mounting Type	Through Hole
Height - Seated (Max)27.05mmVoltage - Isolation1500VrmsWeight0.688 lb (312.07g)	Termination Style	PC Pin
Voltage - Isolation1500VrmsWeight0.688 lb (312.07g)	Size / Dimension	63.50mm L x 50.80mm W
Weight 0.688 lb (312.07g)	Height - Seated (Max)	27.05mm
-	Voltage - Isolation	1500Vrms
Report errors?	Weight	0.688 lb (312.07g)
		Report errors?

LP24-500B10 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

LP24-500B10 Payment Methods



LP24-500B10 Shipping Methods



If you have any question about LP24-500B10, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com