

LPJ-150SPI

LPJ-150SPI Information



For Reference Only

rt Number	LPJ-150SPI	
anufacturer	Eaton	
itegory	Circuit Protection Electrical, Specialty Fuses	
scription	FUSE CRTRDGE 150A 600VAC/300VDC	
ckage	Cylindrical, Alarm Indicator, Blade Terminal	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LPJ-150SPI Specifications

ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Alarn Indicator, Blade TerminalSeriesLOW-PEAK? LPJFuse TypeCatridgeCurrent Rating500Voltage Rating - AC600VVoltage Rating - DCSlowApplicationsElectrical, IndustrialFeaturesSlowClarsJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Alarn Indicator, Blade TerminalSize / Dimension1,500" Dia x 3.000" L (38.10mm x 76.20mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Alarm Indicator, Blade TerminalSeriesLOW-PEAK? LPJFuse TypeCartridgeCurrent Rating150AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Manufacturer Part Number	LPJ-150SPI
Current RatingElectrical, Specialty FusesPackageCylindrical, Alarm Indicator, Blade TerminalSeriesLOW-PEAK? LPJFuse TypeCartridgeCurrent Rating150AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Manufacturer	Eaton
PackageCylindrical, Alarm Indicator, Blade TerminalSeriesLOW-PEAK? LPJFuse TypeCartridgeCurrent Rating150AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Di ax 3.000" L (38.10mm x 76.20mm)	Category	Circuit Protection
SeriesLOW-PEAK? LPJFuse TypeCartridgeCurrent Rating150AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / Case1,500" Dia x 3.000" L (38.10mm x 76.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeFuse TypeCartridgeCurrent Rating150AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300KA AC, 100KA DCMounting TypeBolt MountPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Package	Cylindrical, Alarm Indicator, Blade Terminal
Current Rating150ACurrent Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Series	LOW-PEAK? LPJ
Voltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Fuse Type	Cartridge
Voltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Current Rating	150A
Response TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Voltage Rating - AC	600V
ApplicationsElectrical, IndustrialApplicationsIndicatingFeaturesIndicatingClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Voltage Rating - DC	300V
IndicatingFeaturesIndicatingClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Response Time	Slow
ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Class	1
Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Approvals	CE, CSA, UL
Mounting TypeBolt MountPackage / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Operating Temperature	-
Package / CaseCylindrical, Alarm Indicator, Blade TerminalSize / Dimension1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Breaking Capacity @ Rated Voltage	300kA AC, 100kA DC
Size / Dimension 1.500" Dia x 3.000" L (38.10mm x 76.20mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Alarm Indicator, Blade Terminal
Report errors?	Size / Dimension	1.500" Dia x 3.000" L (38.10mm x 76.20mm)
Toport division		Report errors?

LPJ-150SPI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

LPJ-150SPI Payment Methods Image: I

If you have any question about LPJ-150SPI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com