

### **LPS104-M Information**

Part Number LPS104-M

Manufacturer Artesyn Embedded Technologies

Category Power Supplies - External/Internal (Off-Board)

**AC DC Converters** 

**Description** AC/DC CONVERTER 15V 100W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **LPS104-M Specifications**

Manufacturer Part Number         LPS 104-M           Manufacturer         Artesyn Embedded Technologies           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         LPS 100-M           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.7A           Power (Watts)         100W (150W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         88%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         LPS100-M           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.7A           Power (Watts)         100W (150W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         88%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Manufacturer Part Number	LPS104-M
Package         -           Series         LPS100-M           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.7A           Power (Watts)         100W (150W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         88%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Manufacturer	Artesyn Embedded Technologies
Package         -           Series         LPS100-M           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.7A           Power (Watts)         100W (150W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         88%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         LPS100-M           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.7A           Power (Watts)         100W (150W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         88%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)		AC DC Converters
TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)6.7APower (Watts)100W (150W Forced Air)ApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency88%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Package	-
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC  Voltage - Output 1 15V  Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A  Power (Watts) 100W (150W Forced Air)  Applications ITE (Commercial), Medical  Voltage - Isolation 4kV (4000V)  Efficiency 88%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Series	LPS100-M
Voltage - Input  Voltage - Output 1  15V  Voltage - Output 2  - Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input  Mounting Type  Size / Dimension  4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Type	Open Frame
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  88%  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  15V  15V  15V  16V  15V  16V  16V  16V	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max) 6.7A  Power (Watts) 100W (150W Forced Air)  Applications ITE (Commercial), Medical  Voltage - Isolation 4kV (4000V)  Efficiency 88%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Voltage - Output 1	15V
Voltage - Output 4 Current - Output (Max) 6.7A Power (Watts) 100W (150W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Voltage - Output 2	-
Current - Output (Max) 6.7A  Power (Watts) 100W (150W Forced Air)  Applications ITE (Commercial), Medical  Voltage - Isolation 4kV (4000V)  Efficiency 88%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  88%  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Voltage - Output 4	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Current - Output (Max)	6.7A
Voltage - Isolation 4kV (4000V)  Efficiency 88%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Power (Watts)	100W (150W Forced Air)
Efficiency 88%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Applications	ITE (Commercial), Medical
Operating Temperature  0°C ~ 70°C (With Derating)  Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Voltage - Isolation	4kV (4000V)
Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Efficiency	88%
Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)	Features	Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input
	Mounting Type	Chassis Mount
	Size / Dimension	4.00" L x 2.00" W x 1.29" H (101.6mm x 50.8mm x 32.8mm)
Report errors?		Report errors?

#### **LPS104-M Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **LPS104-M Payment Methods**



















### **LPS104-M Shipping Methods**













If you have any question about LPS104-M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com