



LQR2W472MSEG Information



For Reference Only

Part Number LQR2W472MSEG

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 4700UF 20% 450V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LQR2W472MSEG Specifications

Manufacturer Part Number LQR2W472MSEG Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series LQR Capacitance 4700µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - ESR (Equivalent Series Resistance) - Uperating Temperature 5000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 16.5A @ 120Hz Ripple Current - High Frequency 23.1A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 6.811" (173.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	_	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series LQR Capacitance 4700µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency Lead Spacing Size / Dimension Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	LQR2W472MSEG
Package Radial, Can - Screw Terminals Series LQR Capacitance 4700μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 16.5A @ 120Hz Ripple Current - High Frequency 23.1A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 6.811" (173.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	Nichicon
Package Radial, Can - Screw Terminals Series LQR Capacitance 4700µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 16.5A @ 120Hz Ripple Current - High Frequency 23.1A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 6.811" (173.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Category	Capacitors
Series LQR Capacitance 4700µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 16.5A @ 120Hz Ripple Current - High Frequency 23.1A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 6.811" (173.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 4700μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 16.5A @ 120Hz Ripple Current - High Frequency 23.1A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 6.811" (173.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 16.5A @ 120Hz Ripple Current - High Frequency 23.1A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 6.811" (173.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	LQR
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 16.5A @ 120Hz Ripple Current - High Frequency 23.1A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 4.811" (173.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Capacitance	4700μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 16.5A @ 120Hz Ripple Current - High Frequency 23.1A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 4.590" Dia (63.50mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 16.5A @ 120Hz Rippedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 4.811" (173.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case 5000 Hrs @ 85°C 6000 Hrs @ 85° 6000 Hrs @ 85° 6000 Hrs @ 85° 6000 Hrs @ 85° 6000 Hrs @ 85°	Voltage - Rated	450V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 16.5A @ 120Hz Ripple Current - High Frequency 23.1A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 4.500" Dia (63.50mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 16.5A @ 120Hz Ripple Current - High Frequency 23.1A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 6.811" (173.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	5000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 16.5A @ 120Hz Ripple Current - High Frequency 23.1A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 5urface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 23.1A @ 10kHz Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 6.811" (173.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 6.811" (173.00mm) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	16.5A @ 120Hz
Lead Spacing 1.126" (28.60mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 6.811" (173.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	23.1A @ 10kHz
Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 6.811" (173.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.126" (28.60mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.500" Dia (63.50mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	6.811" (173.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
D	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

LQR2W472MSEG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LQR2W472MSEG Payment Methods



















LQR2W472MSEG Shipping Methods













If you have any question about LQR2W472MSEG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com