

LR4-1300SSF Information



For Reference Only

Part Number LR4-1300SSF

Manufacturer Littelfuse Inc.

Category Circuit Protection
PTC Resettable Fuses

Description POLYSWITCH PTC RESET 13A STRAP

Package Strap

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LR4-1300SSF Specifications

Manufacturer Part Number LR4-1300SSF Manufacturer Littelfuse Inc. Category Circuit Protection PTC Resettable Fuses Package Strap Series PolySwitch?, LR4 Type Polymeric Voltage - Max 20V Current - Max 100A Current - Hold (lh) (Max) 13A Current - Trip (lt) 21.2A Time to Trip 10s Resistance - Initial (Ri) (Min) 3.5 mOhms Resistance - Post Trip (R1) (Max) 9 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	*	
Category Circuit Protection Package Strap Series PolySwitch?, LR4 Type Polymeric Voltage - Max 20V Current - Max 100A Current - Hold (Ih) (Max) 13A Current - Trip (It) 21.2A Time to Trip 10s Resistance - Initial (Ri) (Min) 3.5 mOhms Resistance - Post Trip (R1) (Max) 9 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Manufacturer Part Number	LR4-1300SSF
Package Strap Series PolySwitch?, LR4 Type Polymeric Voltage - Max 20V Current - Max 100A Current - Hold (Ih) (Max) 13A Current - Trip (It) 21.2A Time to Trip 10s Resistance - Initial (Ri) (Min) 3.5 mOhms Resistance - Post Trip (R1) (Max) 9 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Manufacturer	Littelfuse Inc.
Package Strap Series PolySwitch?, LR4 Type Polymeric Voltage - Max 20V Current - Max 100A Current - Hold (lh) (Max) 13A Current - Trip (It) 21.2A Time to Trip 10s Resistance - Initial (Ri) (Min) 3.5 mOhms Resistance - Post Trip (R1) (Max) 9 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Category	Circuit Protection
Series PolySwitch?, LR4 Type Polymeric Voltage - Max 20V Current - Max 100A Current - Hold (lh) (Max) 13A Current - Trip (lt) 21.2A Time to Trip 10s Resistance - Initial (Ri) (Min) 3.5 mOhms Resistance - Post Trip (R1) (Max) 9 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -		PTC Resettable Fuses
Type Polymeric Voltage - Max 20V Current - Max 100A Current - Hold (Ih) (Max) 13A Current - Trip (It) 21.2A Time to Trip 10s Resistance - Initial (Ri) (Min) 3.5 mOhms Resistance - Post Trip (R1) (Max) 9 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Package	Strap
Voltage - Max 20V Current - Max 100A Current - Hold (lh) (Max) 13A Current - Trip (lt) 21.2A Time to Trip 10s Resistance - Initial (Ri) (Min) 3.5 mOhms Resistance - Post Trip (R1) (Max) 9 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Series	PolySwitch?, LR4
Current - Max 100A Current - Hold (lh) (Max) 13A Current - Trip (lt) 21.2A Time to Trip 10s Resistance - Initial (Ri) (Min) 3.5 mOhms Resistance - Post Trip (R1) (Max) 9 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Туре	Polymeric
Current - Hold (Ih) (Max) 13A Current - Trip (It) 21.2A Time to Trip 10s Resistance - Initial (Ri) (Min) 3.5 mOhms Resistance - Post Trip (R1) (Max) 9 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Voltage - Max	20V
Current - Trip (It) 21.2A Time to Trip 10s Resistance - Initial (Ri) (Min) 3.5 mOhms Resistance - Post Trip (R1) (Max) 9 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Current - Max	100A
Time to Trip 10s Resistance - Initial (Ri) (Min) 3.5 mOhms Resistance - Post Trip (R1) (Max) 9 mOhms Resistance - 25°C (Typ)	Current - Hold (Ih) (Max)	13A
Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) 9 mOhms Resistance - 25°C (Typ) - 40°C ~ 85°C Ratings - Wounting Type User Defined Package / Case Size / Dimension Lead Spacing 3.5 mOhms 3.5 mOhms 3.5 mOhms 3.5 mOhms 3.5 mOhms 4 mO	Current - Trip (It)	21.2A
Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing 9 mOhms 9 mOhms 9 mOhms 9 mOhms 9 mOhms 1	Time to Trip	10s
Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing - - - - - - - - - - - - -	Resistance - Initial (Ri) (Min)	3.5 mOhms
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Resistance - Post Trip (R1) (Max)	9 mOhms
Ratings - User Defined Package / Case Strap Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) Lead Spacing	Resistance - 25°C (Typ)	-
Mounting Type User Defined Package / Case Strap Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Operating Temperature	-40°C ~ 85°C
Package / Case Strap Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Ratings	-
Size / Dimension 2.520" L x 0.382" W (64.00mm x 9.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Mounting Type	User Defined
Height - Seated (Max) Thickness (Max) Lead Spacing -	Package / Case	Strap
Thickness (Max) - Lead Spacing -	Size / Dimension	2.520" L x 0.382" W (64.00mm x 9.70mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	-
Report errors?	Lead Spacing	-
report errors.		Report errors?

LR4-1300SSF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LR4-1300SSF Payment Methods



















LR4-1300SSF Shipping Methods













If you have any question about LR4-1300SSF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com