



LRLI-27-350-R-00-20-A Information



For Reference Only

Part Number LRLI-27-350-R-00-20-A Manufacturer Alliance Sensors Group Category Sensors, Transducers

Position Sensors - Angle, Linear Position Measuring

Description ROD ENDS, 14" RANGE, 4-20MA, AL2

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LRLI-27-350-R-00-20-A Specifications

Manufacturer Part Number LRLI-27-350-R-00-20-A Manufacturer Alliance Sensors Group Category Sensors, Transducers Position Sensors - Angle, Linear Position Measuring Package - Series LR For Measuring Linear Position Technology LVIT (Linear Variable Inductance Transducer) Rotation Angle - Electrical, Mechanical - Linear Range 0 ~ 355.60mm (0 ~ 14.00") Output 4mA ~ 20mA Output Signal - Actuator Type Round Shaft Linearity ±0.15% Resistance - Resistance Tolerance - Voltage - Supply - Mounting Type Chassis Mount Termination Style Cable Operating Temperature -20°C ~ 85°C		
CategorySensors, TransducersPackage-SeriesLRFor MeasuringLinear PositionTechnologyLVIT (Linear Variable Inductance Transducer)Rotation Angle - Electrical, Mechanical-Linear Range0 ~ 355.60mm (0 ~ 14.00")Output4mA ~ 20mAOutput Signal-Actuator TypeRound ShaftLinearity±0.15%Resistance-Resistance Tolerance-Voltage - Supply-Mounting TypeChassis MountTermination StyleCableOperating Temperature-20°C ~ 85°C	Manufacturer Part Number	LRLI-27-350-R-00-20-A
Package Series LR For Measuring Linear Position Echnology Rotation Angle - Electrical, Mechanical Linear Range 0 ~ 355.60mm (0 ~ 14.00") Output 4mA ~ 20mA Output Signal Actuator Type Rositance Linearity Resistance Linearity Resistance Resistance Resistance Colerance Voltage - Supply Mounting Type Chassis Mount Termination Style Operating Temperature Position Sensors - Angle, Linear Position Measuring LINEAR ROSITION Measuring LINEAR ROSITION Measuring ACR ROSITION Measuring Linear Position Measuring LINEAR POSITION Measuring ACR ACR ACR ACR ACR ACR ACR AC	Manufacturer	Alliance Sensors Group
Package - LR For Measuring Linear Position Technology LVIT (Linear Variable Inductance Transducer) Rotation Angle - Electrical, Mechanical - Linear Range 0 ~ 355.60mm (0 ~ 14.00") Output 4mA ~ 20mA Output Signal - Round Shaft Linearity £0.15% Resistance 1 - Resistance 1 - Chassis Mount Termination Style Cable Operating Temperature - 20°C ~ 85°C	Category	Sensors, Transducers
SeriesLRFor MeasuringLinear PositionTechnologyLVIT (Linear Variable Inductance Transducer)Rotation Angle - Electrical, Mechanical-Linear Range0 ~ 355.60mm (0 ~ 14.00")Output4mA ~ 20mAOutput Signal-Actuator TypeRound ShaftLinearity±0.15%Resistance-Resistance Tolerance-Voltage - Supply-Mounting TypeChassis MountTermination StyleCableOperating Temperature-20°C ~ 85°C		Position Sensors - Angle, Linear Position Measuring
For Measuring Linear Position LVIT (Linear Variable Inductance Transducer) Rotation Angle - Electrical, Mechanical Linear Range 0 ~ 355.60mm (0 ~ 14.00") Output 4mA ~ 20mA Output Signal - Actuator Type Round Shaft Linearity ±0.15% Resistance - Resistance Resistance - Voltage - Supply Mounting Type Chassis Mount Termination Style Operating Temperature Linear Variable Inductance Transducer) - Linear Variable Inductance Transducer) - Lough Inductance Transducer) - Lough Inductance Transducer) - Lough Inductance Transducer) - Chassis Mount Cable Operating Temperature	Package	-
Technology Rotation Angle - Electrical, Mechanical Linear Range 0 ~ 355.60mm (0 ~ 14.00") Output 4mA ~ 20mA Output Signal - Actuator Type Round Shaft Linearity ±0.15% Resistance Resistance Tolerance - Voltage - Supply Mounting Type Chassis Mount Termination Style Operating Temperature LVIT (Linear Variable Inductance Transducer) - LVIT (Linear Variable Inductance Transducer) LVIT (Linear Variable Inductance Transducer) - LVIT (Linear Variable Inductance Transducer) - LVIT (Linear Variable Inductance Transducer) - Cable - Cable - Operating Temperature	Series	LR
Rotation Angle - Electrical, Mechanical Linear Range 0 ~ 355.60mm (0 ~ 14.00") Output 4mA ~ 20mA Output Signal - Actuator Type Round Shaft Linearity ±0.15% Resistance - Resistance Tolerance Voltage - Supply Mounting Type Chassis Mount Termination Style Operating Temperature - Concept Supply - Cable -20°C ~ 85°C	For Measuring	Linear Position
Linear Range0 ~ 355.60mm (0 ~ 14.00")Output4mA ~ 20mAOutput Signal-Actuator TypeRound ShaftLinearity±0.15%Resistance-Resistance Tolerance-Voltage - Supply-Mounting TypeChassis MountTermination StyleCableOperating Temperature-20°C ~ 85°C	Technology	LVIT (Linear Variable Inductance Transducer)
Output Signal - Actuator Type Round Shaft Linearity ±0.15% Resistance - Resistance Tolerance - Voltage - Supply - Mounting Type Chassis Mount Termination Style Cable Operating Temperature -20°C ~ 85°C	Rotation Angle - Electrical, Mechanical	-
Output Signal - Actuator Type Round Shaft Linearity ±0.15% Resistance - Resistance Tolerance - Voltage - Supply - Mounting Type Chassis Mount Termination Style Cable Operating Temperature -20°C ~ 85°C	Linear Range	0 ~ 355.60mm (0 ~ 14.00")
Actuator TypeRound ShaftLinearity±0.15%Resistance-Resistance Tolerance-Voltage - Supply-Mounting TypeChassis MountTermination StyleCableOperating Temperature-20°C ~ 85°C	Output	4mA ~ 20mA
Linearity ±0.15% Resistance - Resistance Tolerance - Voltage - Supply - Mounting Type Chassis Mount Termination Style Cable Operating Temperature -20°C ~ 85°C	Output Signal	-
Resistance Tolerance - Voltage - Supply - Mounting Type Chassis Mount Termination Style Cable Operating Temperature -20°C ~ 85°C	Actuator Type	Round Shaft
Resistance Tolerance - Voltage - Supply - Mounting Type Chassis Mount Termination Style Cable Operating Temperature -20°C ~ 85°C	Linearity	±0.15%
Voltage - Supply Mounting Type Chassis Mount Termination Style Cable Operating Temperature -20°C ~ 85°C	Resistance	-
Mounting TypeChassis MountTermination StyleCableOperating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Resistance Tolerance	-
Termination Style Cable Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Voltage - Supply	-
Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Mounting Type	Chassis Mount
	Termination Style	Cable
Report errors?	Operating Temperature	-20°C ~ 85°C
		Report errors?

LRLI-27-350-R-00-20-A Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LRLI-27-350-R-00-20-A Payment Methods



















LRLI-27-350-R-00-20-A Shipping Methods













If you have any question about LRLI-27-350-R-00-20-A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com