



LS127C2D-T Information



For Reference Only

Part Number LS127C2D-T Manufacturer Citizen

Category Switches

Tactile Switches

Description SWITCH TACT SPST-NO 0.02A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LS127C2D-T Specifications

Manufacturer Part Number L\$127C2D-T Manufacturer Citizen Category Switches Package - Series L\$127 Circuit SPST-NO Switch Function Off-Mom Conact Rating @ Voltage 0.02A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.60mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style SMD (SMT) Tab Outline 3.20mm x 2.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features - Report errors?		
Category Switches Package - Series LS127 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.02A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.60mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style SMD (SMT) Tab Outline 3.20mm x 2.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features -	Manufacturer Part Number	LS127C2D-T
Package - Series LS127 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.02A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.60mm Actuator Length, Right Angle - Top Actuated Termination Style SMD (SMT) Tab Outline 3.20mm x 2.00mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features	Manufacturer	Citizen
Package - Series LS127 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.02A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.60mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style SMD (SMT) Tab Outline 3.20mm x 2.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features -	Category	Switches
Series LS127 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.02A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.60mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style SMD (SMT) Tab Outline 3.20mm x 2.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features -		Tactile Switches
Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.02A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.60mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style SMD (SMT) Tab Outline 3.20mm x 2.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features -	Package	-
Switch FunctionOff-MomContact Rating @ Voltage0.02A @ 12VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical0.60mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleSMD (SMT) TabOutline3.20mm x 2.00mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-Features-	Series	LS127
Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style SMD (SMT) Tab Outline Surface Mount Top Actuated Tom Actuated Termination Style SMD (SMT) Tab Outline Surface Mount Top Actuated Tom Actuated Top Actuated Tom Actuated Top Actuat	Circuit	SPST-NO
Actuator Type Surface Mount Actuator Height off PCB, Vertical 0.60mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style SMD (SMT) Tab Outline 3.20mm x 2.00mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features - Standard Standard Standard Surface Mount 0.60mm Actuator One Top Actuated Top Actuated SMD (SMT) Tab SMD (SMT) Tab 1.00mm x 2.00mm Actuator Orientation Top Actuated	Switch Function	Off-Mom
Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Surface Mount Surface Mount Surface Mount Surface Mount Actuator Oientation Actuator Orientation Top Actuated SMD (SMT) Tab Surface Mount Actuator Mount Fop Actuated Top Actuated Non-Illuminated Non-Illuminated Features Ingress Protection Features	Contact Rating @ Voltage	0.02A @ 12VDC
Actuator Height off PCB, Vertical 0.60mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style SMD (SMT) Tab Outline 3.20mm x 2.00mm Illumination Illuminated Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features -	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated SMD (SMT) Tab SMD (SMT) Tab 3.20mm x 2.00mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style SMD (SMT) Tab Outline 3.20mm x 2.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features	Actuator Height off PCB, Vertical	0.60mm
Termination Style Outline 3.20mm x 2.00mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features SMD (SMT) Tab SMD (SMT) Tab Show 2.00mm Non-Illuminated - Ingress Postection - Ingress Protection - Features	Actuator Length, Right Angle	-
Outline 3.20mm x 2.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-Features-	Termination Style	SMD (SMT) Tab
Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features	Outline	3.20mm x 2.00mm
Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-Features-	Illumination	Non-Illuminated
Operating Force 160gf Ingress Protection - Features -	Illumination Type, Color	-
Ingress Protection - Features -	Illumination Voltage (Nominal)	-
Features -	Operating Force	160gf
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

LS127C2D-T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LS127C2D-T Payment Methods





















LS127C2D-T Shipping Methods













If you have any question about LS127C2D-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com