



LS12P2E-T Information

www.elsener.com

For Reference Only

Part Number LS12P2E-T
Manufacturer Citizen
Category Switches

Tactile Switches

Description SWITCH TACT SPST-NO 0.02A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LS12P2E-T Specifications

Manufacturer Part Number LS12P2E-T Manufacturer Citizen Category Switches Package - Series LS12P Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.02A @ 12VDC Actuator Type Rectangular Button Mounting Type Surface Mount Actuator Height off PCB, Vertical 1.35mm Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style SMD (SMT) Tab Outline 5.35mm x 3.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features - Report errors?		
CategorySwitchesPackage-SeriesLS12PCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.02A @ 12VDCActuator TypeRectangular ButtonMounting TypeSurface MountActuator Height off PCB, Vertical1.35mmActuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleSMD (SMT) TabOutline5.35mm x 3.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Fore160gfIngress Protection-Features-	Manufacturer Part Number	LS12P2E-T
Package - Series LS12P Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.02A @ 12VDC Actuator Type Rectangular Button Mounting Type Surface Mount Actuator Height off PCB, Vertical 1.35mm Actuator Length, Right Angle - Side Actuated Termination Style SMD (SMT) Tab Outline 5.35mm x 3.50mm Illumination Unique (Nominal) - Illuminated Illumination Voltage (Nominal) - Illumination Voltage (Nominal) - Illumination Features Indeed Indeed Ingress Protection -	Manufacturer	Citizen
Package - Series LS12P Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.02A @ 12VDC Actuator Type Rectangular Button Mounting Type Surface Mount Actuator Height off PCB, Vertical 1.35mm Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style SMD (SMT) Tab Outline 5.35mm x 3.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features -	Category	Switches
Series LS12P Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.02A @ 12VDC Actuator Type Rectangular Button Mounting Type Surface Mount Actuator Height off PCB, Vertical 1.35mm Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style SMD (SMT) Tab Outline 5.35mm x 3.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features -		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.02A @ 12VDCActuator TypeRectangular ButtonMounting TypeSurface MountActuator Height off PCB, Vertical1.35mmActuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleSMD (SMT) TabOutline5.35mm x 3.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-Features-	Package	-
Switch FunctionOff-MomContact Rating @ Voltage0.02A @ 12VDCActuator TypeRectangular ButtonMounting TypeSurface MountActuator Height off PCB, Vertical1.35mmActuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleSMD (SMT) TabOutline5.35mm x 3.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-Features-	Series	LS12P
Contact Rating @ Voltage 0.02A @ 12VDC Actuator Type Rectangular Button Mounting Type Surface Mount Actuator Height off PCB, Vertical 1.35mm Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style SMD (SMT) Tab Outline 5.35mm x 3.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features - Features -	Circuit	SPST-NO
Actuator Type Rectangular Button Mounting Type Surface Mount Actuator Height off PCB, Vertical 1.35mm Actuator Length, Right Angle - Actuator Orientation Side Actuated Termination Style SMD (SMT) Tab Outline 5.35mm x 3.50mm Illumination Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features - Features - Rectangular Button Rectangular Button Rectangular Button Rectangular Button Surface Mount 1.35mm Actuator Cheen Side Actuated Side Actuated To Actuated Side Actuated To Actuated Side Actuated To Actuated Side Actuated Side Actuated Side Actuated Side Actuated Side Actuated To Actuator Orientation Side Actuated Side Actuate	Switch Function	Off-Mom
Mounting TypeSurface MountActuator Height off PCB, Vertical1.35mmActuator Length, Right Angle-Actuator OrientationSide ActuatedTermination StyleSMD (SMT) TabOutline5.35mm x 3.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-Features-	Contact Rating @ Voltage	0.02A @ 12VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Side Actuated Termination Style Outline SMD (SMT) Tab Outline 5.35mm x 3.50mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features 1.35mm 1.3	Actuator Type	Rectangular Button
Actuator Length, Right Angle Actuator Orientation Side Actuated SMD (SMT) Tab SMD (SMT) Tab Outline 5.35mm x 3.50mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features	Mounting Type	Surface Mount
Actuator Orientation Side Actuated SMD (SMT) Tab Outline 5.35mm x 3.50mm Illumination Non-Illuminated Illumination Type, Color -Illumination Voltage (Nominal) Operating Force Ingress Protection Features - Side Actuated SMD (SMT) Tab 5.35mm x 3.50mm Non-Illuminated	Actuator Height off PCB, Vertical	1.35mm
Termination Style Outline 5.35mm x 3.50mm Illumination Non-Illuminated - Illumination Voltage (Nominal) Operating Force Ingress Protection Features SMD (SMT) Tab 5.35mm x 3.50mm Non-Illuminated - - - - - - - - - - - - -	Actuator Length, Right Angle	-
Outline 5.35mm x 3.50mm Illumination Non-Illuminated	Actuator Orientation	Side Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-Features-	Termination Style	SMD (SMT) Tab
Illumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gfIngress Protection-Features-	Outline	5.35mm x 3.50mm
Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection - Features -	Illumination	Non-Illuminated
Operating Force 160gf Ingress Protection - Features -	Illumination Type, Color	-
Ingress Protection - Features -	Illumination Voltage (Nominal)	-
Features -	Operating Force	160gf
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

LS12P2E-T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LS12P2E-T Payment Methods





















LS12P2E-T Shipping Methods













If you have any question about LS12P2E-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com