

LS75-36 Information



For Reference Only

Part Number LS75-36

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 36V 75W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TC	75	36	Cn	ooi	fiaa	tion	
L)/5:	. 90	5 D	ecu	uca	uon	IS

Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Scries LS Type Enclosed Number of Outputs 1 Voltage - Input 88 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)						
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series LS Type Enclosed Number of Outputs 1 Voltage - Input 88 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Manufacturer Part Number	LS75-36				
Package - Series LS Type Enclosed Number of Outputs 1 Voltage - Input 88 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Manufacturer	TDK-Lambda Americas Inc.				
Package - Series LS Type Enclosed Number of Outputs 1 Voltage - Input 88 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Category	Power Supplies - External/Internal (Off-Board)				
Series LS Type Enclosed Number of Outputs 1 Voltage - Input 88 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)		AC DC Converters				
Type Enclosed Number of Outputs 1 Voltage - Input 88 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Package	-				
Number of Outputs 1 Voltage - Input 88 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Series	LS				
Voltage - Input 88 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.1A Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Туре	Enclosed				
Voltage - Output 136VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.1APower (Watts)75WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency86%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Number of Outputs	1				
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - Universal Size / Dimension Size / Dimension Current - Output 4 - C	Voltage - Input	88 ~ 264 VAC				
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Voltage - Output 1	36V				
Voltage - Output 4-Current - Output (Max)2.1APower (Watts)75WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency86%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Voltage - Output 2	-				
Current - Output (Max) Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Voltage - Output 3	-				
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Voltage - Output 4	-				
ApplicationsITE (Commercial)Voltage - Isolation $3kV (3000V)$ Efficiency 86% Operating Temperature $-25^{\circ}C \sim 70^{\circ}C$ (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension 5.10° L x 3.80° W x 1.50° H (129.5mm x 96.5 mm x 38.1 mm)	Current - Output (Max)	2.1A				
Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Power (Watts)	75W				
Efficiency 86% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Applications	ITE (Commercial)				
Operating Temperature -25°C ~ 70°C (With Derating) Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Voltage - Isolation	3kV (3000V)				
Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Efficiency	86%				
Mounting Type Chassis Mount Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Operating Temperature	-25°C ~ 70°C (With Derating)				
Size / Dimension 5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)	Features	Adjustable Output, DC Input Capable, Universal Input				
	Mounting Type	Chassis Mount				
Report errors?	Size / Dimension	5.10" L x 3.80" W x 1.50" H (129.5mm x 96.5mm x 38.1mm)				
			Report errors?			

LS75-36 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LS75-36 Payment Methods



















LS75-36 Shipping Methods













If you have any question about LS75-36, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com