



LSRK030.T Information

Part Number LSRK030.T Manufacturer Littelfuse Inc. Category Circuit Protection Heisener.com

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 30A 600VAC/300VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LSRK030.T Specifications

Manufacturer Part NumberLSRK030.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesPOWR-GARD?, POWR-PRO? LLSRKFuse TypeCartridgeCurrent Rating30AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRKIApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)Report errors?		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?, POWR-PRO? LLSRKFuse TypeCartridgeCurrent Rating30AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Manufacturer Part Number	LSRK030.T
Beaking Capacity @ Rated Voltage Electrical, Specialty Fuses Cartridge, Non-Standard POWR-GARD?, POWR-PRO? LLSRK Fuse Type Cartridge Current Rating 30A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Electrical, Industrial Features - CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage CoukA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD?, POWR-PRO? LLSRKFuse TypeCartridgeCurrent Rating30AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Category	Circuit Protection
SeriesPOWR-GARD?, POWR-PRO? LLSRKFuse TypeCartridgeCurrent Rating30AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating30AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Sign (20,000 m x 127,000 mm) 300V Response Sign (300V Response Sign (300V Response Sign (300V Si	Series	POWR-GARD?, POWR-PRO? LLSRK
Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 6	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 300V 300V 300V 300V AV Blow Electrical, Industrial - CE, CSA, QPL, UL - C	Current Rating	30A
Response Time Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Electrical, Industrial - CE, CSA, QPL UL CE, CSA, QPL, UL	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Voltage Rating - DC	300V
Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Country @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Response Time	Slow
Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension CE, CSA, QPL, UL - CE, CSA, QPL - CE,	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Class	RK1
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 5.000" L (20.60mm x 127.00mm)
		Report errors?

LSRK030.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LSRK030.T Payment Methods



















LSRK030.T Shipping Methods













If you have any question about LSRK030.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com