



# LSRK060.TXID Information

Heisener.com

Part NumberLSRK060.TXIDManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 60A 600VAC/300VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## LSRK060.TXID Specifications

Manufacturer Part NumberLSRK060.TXIDManufacturerLittelfuse Inc.CategoryCircuit ProtectionBackageCartridge, Non-StandardSeriesPOWR-GARD?, POWR-PRO? LLSRK_IDFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 5.500" L (27.00mm x 139.70mm)Report errors?		
CategoryCircuit ProtectionBeckrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?, POWR-PRO? LLSRK_IDFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Manufacturer Part Number	LSRK060.TXID
Electrical, Specialty Fuses  Package Cartridge, Non-Standard Series POWR-GARD?, POWR-PRO? LLSRK_ID  Fuse Type Cartridge Current Rating 60A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature  Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension  Electrical, Industrial Features Cartridge, Non-Standard Size / Dimension  LOG3" Dia x 5.500" L (27.00mm x 139.70mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD?, POWR-PRO? LLSRK_IDFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Category	Circuit Protection
SeriesPOWR-GARD?, POWR-PRO? LLSRK_IDFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 5.500" L (27.00mm x 139.70mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating60AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Package	Cartridge, Non-Standard
Current Rating  Current Rating 60A  Voltage Rating - AC  600V  Voltage Rating - DC  300V  Response Time  Slow  Applications  Electrical, Industrial  Features  Indicating  Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  60A  60A  60A  60B  60A  60B  60V  60B  60V  60B  60B  60B  60B	Series	POWR-GARD?, POWR-PRO? LLSRK_ID
Voltage Rating - AC  Voltage Rating - DC  300V  Response Time  Slow  Applications  Electrical, Industrial  Features  Indicating  Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  600	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Slow  Applications Electrical, Industrial  Features Indicating Class RK1  Approvals CE, CSA, QPL, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  300V  300V  300V  300V  8100  Slow  1000  Slow	Current Rating	60A
Response Time  Applications  Electrical, Industrial  Features  Indicating  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Slow  Slow  Slow  Slow  Slow  Slow  Slow  Slow  Electrical, Industrial  Indicating  RK1  APPROVAL  CE, CSA, QPL, UL  CE, CS	Voltage Rating - AC	600V
Applications Electrical, Industrial Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Voltage Rating - DC	300V
Features Indicating Class RK1  Approvals CE, CSA, QPL, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Response Time	Slow
Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Applications	Electrical, Industrial
Approvals  CE, CSA, QPL, UL  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  CE, CSA, QPL, UL  CRACK OPL, UL  CRACK OPL  CRACK OPL, UL  CRACK OPL  CRA	Features	Indicating
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Class	RK1
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	1.063" Dia x 5.500" L (27.00mm x 139.70mm)
		Report errors?

### LSRK060.TXID Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## LSRK060.TXID Payment Methods



















### LSRK060.TXID Shipping Methods













If you have any question about LSRK060.TXID, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com