



### LSRK080.V Information

(A) Heisener.com

Part Number LSRK080.V

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 80A 600VAC/300VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## LSRK080.V Specifications

Manufacturer Part NumberLSRK080.VManufacturerLittelfuse Inc.CategoryCircuit ProtectionBelectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? LLSRKFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 7.874" L (33.30mm x 200.00mm)		
Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminals  Series  POWR-GARD?, POWR-PRO? LLSRK  Fuse Type  Cartridge  Current Rating  80A  Voltage Rating - AC  600V  Voltage Rating - DC  300V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Cylindrical, Blade Terminals  Size / Dimension  Circuit Protection  Electrical, Industrial  Capacity Grape (Capacity Grape)  Cylindrical, Blade Terminals  1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Manufacturer Part Number	LSRK080.V
Blectrical, Specialty Fuses  Package Cylindrical, Blade Terminals Series POWR-GARD?, POWR-PRO? LLSRK Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension  Electrical, Industrial Cylindrical, Blade Terminals Size / Dimension  1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? LLSRKFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Category	Circuit Protection
Series POWR-GARD?, POWR-PRO? LLSRK Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Package	Cylindrical, Blade Terminals
Current Rating 80A  Voltage Rating - AC 600V  Voltage Rating - DC 300V  Response Time Slow  Applications Electrical, Industrial  Features - Class RK1  Approvals CE, CSA, QPL, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Series	POWR-GARD?, POWR-PRO? LLSRK
Voltage Rating - AC  Voltage Rating - DC  300V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  6	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  300V  300V  300V  300V  300V  AC, 20kA  CE, CSA, CPL, UL  CE, CSA, QPL, UL  CE, CSA, CE,	Current Rating	80A
Response Time Applications Electrical, Industrial  Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Slow Electrical, Industrial  Electrical, Industrial  - CE, CSA, QPL, UL  - CE, CSA, QPL  - CE, CSA, QPL  - CE	Voltage Rating - AC	600V
Applications  Features  Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  Electrical, Industrial  -  RK1  CE, CSA, QPL, UL  -  CE, CSA	Voltage Rating - DC	300V
Features  Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  Size / Dimension  -  1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Response Time	Slow
Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Applications	Electrical, Industrial
Approvals  CE, CSA, QPL, UL  Operating Temperature  - Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Class	RK1
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
	Size / Dimension	1.311" Dia x 7.874" L (33.30mm x 200.00mm)
Report errors?		Report errors?

### LSRK080.V Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# LSRK080.V Payment Methods


































If you have any question about LSRK080.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com