



LSRK080.VXID Information

Heisener.com

Part Number LSRK080.VXID
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 80A 600VAC/300VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LSRK080.VXID Specifications

Manufacturer Part NumberLSRK080.VXIDManufacturerLittelfuse Inc.CategoryCircuit ProtectionBackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? LLSRK_IDFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 7.874" L (33.30mm x 200.00mm)Report errors?		
CategoryCircuit ProtectionBeckrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? LLSRK_IDFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Manufacturer Part Number	LSRK080.VXID
Bectrical, Specialty Fuses Cylindrical, Blade Terminals Series POWR-GARD?, POWR-PRO? LLSRK_ID Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Electrical, Industrial Features Indicating CIASS RK1 APPROVED CY, UL CY, CSA, QPL, UL CY,	Manufacturer	Littelfuse Inc.
Package Cylindrical, Blade Terminals Series POWR-GARD?, POWR-PRO? LLSRK_ID Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Category	Circuit Protection
SeriesPOWR-GARD?, POWR-PRO? LLSRK_IDFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 7.874" L (33.30mm x 200.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 80A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Lasting Cartridge Row	Package	Cylindrical, Blade Terminals
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 800 C00 800 C00 A00 A00 A00 A00	Series	POWR-GARD?, POWR-PRO? LLSRK_ID
Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 600	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 300V 300V 300V 8low 8low 8low 6lectrical, Industrial Features CE, CSA, QPL, UL 90kA AC, 20kA DC Holder Cylindrical, Blade Terminals 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Current Rating	80A
Response Time Applications Electrical, Industrial Features Indicating RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Voltage Rating - AC	600V
Applications Electrical, Industrial Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Voltage Rating - DC	300V
Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Response Time	Slow
Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension CE, CSA, QPL, UL CHARACTOR OF THE PROPERTY OF	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Class	RK1
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	1.311" Dia x 7.874" L (33.30mm x 200.00mm)
		Report errors?

LSRK080.VXID Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LSRK080.VXID Payment Methods



















LSRK080.VXID Shipping Methods













If you have any question about LSRK080.VXID, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com