



LSRK225.X Information

Heisener.com

Part Number LSRK225.X
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 225A 600VAC/300VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LSRK225.X Specifications

Manufacturer Part NumberLSRK225.XManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? LLSRKFuse TypeCartridgeCurrent Rating225AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.843" Dia x 11.626" L (72.20mm x 295.30mm)Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminals Series POWR-GARD?, POWR-PRO? LLSRK Fuse Type Cartridge Current Rating 225A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial Features - CL, CSA, QPL, UL Operating Temperature Poward AC, 20kA DC Holder Cylindrical, Blade Terminals Size / Dimension	Manufacturer Part Number	LSRK225.X
Electrical, Specialty Fuses Package Cylindrical, Blade Terminals Series POWR-GARD?, POWR-PRO? LLSRK Fuse Type Cartridge Current Rating 225A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Electrical, Industrial Features - CE, CSA, QPL, UL CE, CSA, QPL, UL COPERATION OF THE MORE OF THE MO	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? LLSRKFuse TypeCartridgeCurrent Rating225AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.843" Dia x 11.626" L (72.20mm x 295.30mm)	Category	Circuit Protection
SeriesPOWR-GARD?, POWR-PRO? LLSRKFuse TypeCartridgeCurrent Rating225AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.843" Dia x 11.626" L (72.20mm x 295.30mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating225AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.843" Dia x 11.626" L (72.20mm x 295.30mm)	Package	Cylindrical, Blade Terminals
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 225A 600V CE, CSA COV AU CE, CSA CE, CSA CE, CSA COV CE, CSA COV COV COV COV COV COV COV CO	Series	POWR-GARD?, POWR-PRO? LLSRK
Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 300V 600V 6	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 300V 300V 300V 300V 300V 400 AC, 20kA DC 400 401 401 402 400 404 405 406 407 407 408 409 400 400 400 400 400 400	Current Rating	225A
Response Time Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Slow Slow Slow Slow Slow Slow Approvals - CE, CSA, Industrial CE, CSA, QPL, UL - CE, C	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.843" Dia x 11.626" L (72.20mm x 295.30mm)	Voltage Rating - DC	300V
Features - Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.843" Dia x 11.626" L (72.20mm x 295.30mm)	Response Time	Slow
Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.843" Dia x 11.626" L (72.20mm x 295.30mm)	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.843" Dia x 11.626" L (72.20mm x 295.30mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.843" Dia x 11.626" L (72.20mm x 295.30mm)	Class	RK1
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.843" Dia x 11.626" L (72.20mm x 295.30mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.843" Dia x 11.626" L (72.20mm x 295.30mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 2.843" Dia x 11.626" L (72.20mm x 295.30mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 2.843" Dia x 11.626" L (72.20mm x 295.30mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	2.843" Dia x 11.626" L (72.20mm x 295.30mm)
		Report errors?

LSRK225.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LSRK225.X Payment Methods



















LSRK225.X Shipping Methods













If you have any question about LSRK225.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com