



### LSRK450.X Information

Manul Catego Heisener.com

Part NumberLSRK450.XManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 450A 600VAC/300VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# LSRK450.X Specifications

Manufacturer Part NumberLSRK450.XManufacturerLittelfuse Inc.CategoryCircuit ProtectionBeckageCylindrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? LLSRKFuse TypeCartridgeCurrent Rating450AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension3.343" Dia x 13.374" L (84.90mm x 339.70mm)			
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesPOWR-GARD?, POWR-PRO? LLSRKFuse TypeCartridgeCurrent Rating450AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Manufacturer Part Number	LSRK450.X	
Electrical, Specialty Fuses  Cylindrical, Blade Terminals  Series  POWR-GARD?, POWR-PRO? LLSRK  Fuse Type  Cartridge  Current Rating  Voltage Rating - AC  Voltage Rating - DC  Slow  Applications  Electrical, Industrial  Features  - Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  Electrical, Blade Terminals  Subscience  Cylindrical, Blade Terminals  Size / Dimension  Size / Dimension	Manufacturer	Littelfuse Inc.	
Package Cylindrical, Blade Terminals  Series POWR-GARD?, POWR-PRO? LLSRK  Fuse Type Cartridge  Current Rating 450A  Voltage Rating - AC 600V  Voltage Rating - DC 300V  Response Time Slow  Applications Electrical, Industrial  Features -  Class RK1  Approvals CE, CSA, QPL, UL  Operating Temperature -  Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Category	Circuit Protection	
SeriesPOWR-GARD?, POWR-PRO? LLSRKFuse TypeCartridgeCurrent Rating450AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension3.343" Dia x 13.374" L (84.90mm x 339.70mm)		Electrical, Specialty Fuses	
Fuse TypeCartridgeCurrent Rating450AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Package	Cylindrical, Blade Terminals	
Current Rating 450A  Voltage Rating - AC 600V  Voltage Rating - DC 300V  Response Time Slow  Applications Electrical, Industrial  Features -  Class RK1  Approvals CE, CSA, QPL, UL  Operating Temperature -  Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Series	POWR-GARD?, POWR-PRO? LLSRK	
Voltage Rating - AC  Voltage Rating - DC  300V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  6	Fuse Type	Cartridge	
Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  300V  300V  300V  300V  300V  Electrical, Industrial  - CE, CSA, QPL  VL  CE, CSA, QPL, UL  CE	Current Rating	450A	
Response Time  Applications  Electrical, Industrial  Features  - Class  RK1  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  Slow  Slow  Slow  Slow  Slow  Slow  Slow  Slow  Holdstrial  - CE, CSA, QPL, UL  - CE, CSA, QPL  - CE, CSA, QPL  - CE, CSA, QPL  - CE, C	Voltage Rating - AC	600V	
Applications Electrical, Industrial  Features - Class RK1  Approvals CE, CSA, QPL, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Voltage Rating - DC	300V	
Features - Class RK1  Approvals CE, CSA, QPL, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Response Time	Slow	
Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Applications	Electrical, Industrial	
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Features	-	
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Class	RK1	
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Approvals	CE, CSA, QPL, UL	
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Operating Temperature	-	
Package / Case Cylindrical, Blade Terminals Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC	
Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Mounting Type	Holder	
	Package / Case	Cylindrical, Blade Terminals	
Report errors?	Size / Dimension	3.343" Dia x 13.374" L (84.90mm x 339.70mm)	
			Report errors?

#### LSRK450.X Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### LSRK450.X Payment Methods



















# LSRK450.X Shipping Methods













If you have any question about LSRK450.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com