



LSRK600.XXID Information

Heisener.com

Part NumberLSRK600.XXIDManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 600A 600VAC/300VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LSRK600.XXID Specifications

Manufacturer Part NumberLSRK600.XXIDManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? LLSRK_IDFuse TypeCartridgeCurrent Rating600AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension3.343" Dia x 13.374" L (84.90mm x 339.70mm)		
CategoryCircuit ProtectionPackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? LLSRK_IDFuse TypeCartridgeCurrent Rating600AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Manufacturer Part Number	LSRK600.XXID
Electrical, Specialty Fuses Package Cylindrical, Blade Terminals Series POWR-GARD?, POWR-PRO? LLSRK_ID Fuse Type Cartridge Current Rating 600A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Electrical, Blade Terminals S39.70mm x 339.70mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? LLSRK_IDFuse TypeCartridgeCurrent Rating600AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Category	Circuit Protection
Series POWR-GARD?, POWR-PRO? LLSRK_ID Fuse Type Cartridge Current Rating 600A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating600AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK1ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Package	Cylindrical, Blade Terminals
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600A 600V	Series	POWR-GARD?, POWR-PRO? LLSRK_ID
Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 300V 600V 6	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 300V 300V 300V 300V 300V ARA 200k AC, 20kA DC Holder Cylindrical, Blade Terminals 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Current Rating	600A
Response Time Applications Electrical, Industrial Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Slow Slow Slow Slow Slow Slow Slow Slow Slow Approvals CE, CSA, Industrial CE, CSA, QPL, UL CE, CSA	Voltage Rating - AC	600V
Applications Electrical, Industrial Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Voltage Rating - DC	300V
Features Indicating Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature	Response Time	Slow
Class RK1 Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension CE, CSA, QPL, UL CUL CHARTON CONTROL	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Class	RK1
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 3.343" Dia x 13.374" L (84.90mm x 339.70mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	3.343" Dia x 13.374" L (84.90mm x 339.70mm)
		Report errors?

LSRK600.XXID Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LSRK600.XXID Payment Methods



















LSRK600.XXID Shipping Methods













If you have any question about LSRK600.XXID, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com