

LT1365CS#TRPBF

LT1365CS#TRPBF Information



For Reference Only

Part Number LT1365CS#TRPBF
Manufacturer Linear Technology
Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP VFB 70MHZ 16SO **Package** 16-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LT1365CS#TRPBF Specifications

Manufacturer Part Number LT1365CS#TRPBF Manufacturer Linear Technology Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 16-SOIC (0.154", 3.90mm Width) Series C-Load? Amplifier Type Voltage Feedback Number of Circuits 4 Output Type - Slew Rate 1000 V/µs Gain Bandwidth Product 70MHz -3db Bandwidth - Current - Input Bias 600nA Voltage - Input Offset 500µV Current - Supply 6.3mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 5 V ~ 36 V, ±2.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SO		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 16-SOIC (0.154", 3.90mm Width) Series C-Load? Amplifier Type Voltage Feedback Number of Circuits 4 Output Type - Slew Rate 1000 V/μs Gain Bandwidth Product 70MHz -3db Bandwidth - Current - Input Bias 600nA Voltage - Input Offset 500μV Current - Supply 6.3mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 5 V ~ 36 V, ±2.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC (0.154", 3.90mm Width)	Manufacturer Part Number	LT1365CS#TRPBF
Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage16-SOIC (0.154", 3.90mm Width)SeriesC-Load?Amplifier TypeVoltage FeedbackNumber of Circuits4Output Type-Slew Rate1000 V/μsGain Bandwidth Product70MHz-3db Bandwidth-Current - Input Bias600nAVoltage - Input Offset500μVCurrent - Supply6.3mACurrent - Output / Channel60mAVoltage - Supply, Single/Dual (±)5 V ~ 36 V, ±2.5 V ~ 18 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SO	Manufacturer	Linear Technology
Package 16-SOIC (0.154", 3.90mm Width) Series C-Load? Amplifier Type Voltage Feedback Number of Circuits 4 Output Type - Slew Rate 1000 V/μs Gain Bandwidth Product 70MHz -3db Bandwidth - Current - Input Bias 600nA Voltage - Input Offset 500μV Current - Supply 6.3mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 5 V ~ 36 V, ±2.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SO	Category	Integrated Circuits (ICs)
SeriesC-Load?Amplifier TypeVoltage FeedbackNumber of Circuits4Output Type-Slew Rate $1000 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 70MHz -3db Bandwidth-Current - Input Bias 600nA Voltage - Input Offset $500\mu\text{V}$ Current - Supply 6.3mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) $5 \text{ V} \sim 36 \text{ V}, \pm 2.5 \text{ V} \sim 18 \text{ V}$ Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case $16\text{-SOIC (0.154", 3.90mm Width)}$ Supplier Device Package 16-SO		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier TypeVoltage FeedbackNumber of Circuits4Output Type-Slew Rate1000 V/μsGain Bandwidth Product70MHz-3db Bandwidth-Current - Input Bias600nAVoltage - Input Offset500μVCurrent - Supply6.3mACurrent - Output / Channel60mAVoltage - Supply, Single/Dual (±)5 V ~ 36 V, ±2.5 V ~ 18 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SO	Package	16-SOIC (0.154", 3.90mm Width)
Number of Circuits 4 Output Type - Slew Rate 1000 V/μs Gain Bandwidth Product 70MHz -3db Bandwidth - Current - Input Bias 600nA Voltage - Input Offset 500μV Current - Supply 6.3mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 5 V ~ 36 V, ±2.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SO	Series	C-Load?
Output Type Slew Rate 1000 V/µs Gain Bandwidth Product -3db Bandwidth -Current - Input Bias 600nA Voltage - Input Offset 500µV Current - Supply 6.3mA Current - Output / Channel Voltage - Supply, Single/Dual (±) 5 V ~ 36 V, ±2.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Amplifier Type	Voltage Feedback
Slew Rate $1000 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 70MHz - 3db Bandwidth - $-$ Current - Input Bias 600nA Voltage - Input Offset $500 \mu\text{V}$ Current - Supply 6.3mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (\pm) $5 \text{ V} \sim 36 \text{ V}, \pm 2.5 \text{ V} \sim 18 \text{ V}$ Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Mounting Type Surface Mount Package / Case 16-SOIC (0.154° , 3.90mm Width) Supplier Device Package	Number of Circuits	4
Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 600nA Voltage - Input Offset 500μV Current - Supply 6.3mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 5 V ~ 36 V, ±2.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Output Type	-
$-3 db \ Bandwidth \\ -Current - Input \ Bias \\ 600 nA \\ Voltage - Input \ Offset \\ 500 \mu V \\ Current - Supply \\ 6.3 mA \\ Current - Output / Channel \\ 60 mA \\ Voltage - Supply, Single/Dual (\pm) 5 \ V \sim 36 \ V, \pm 2.5 \ V \sim 18 \ V \\ Operating \ Temperature \\ 0^{\circ}C \sim 70^{\circ}C \\ Mounting \ Type \\ Surface \ Mount \\ Package / Case \\ 16-SOIC (0.154", 3.90 mm \ Width) \\ Supplier \ Device \ Package \\ 16-SO \\ \\$	Slew Rate	1000 V/μs
Current - Input Bias $600nA$ Voltage - Input Offset $500\mu V$ Current - Supply $6.3mA$ Current - Output / Channel $60mA$ Voltage - Supply, Single/Dual (\pm) $5 V \sim 36 V$, $\pm 2.5 V \sim 18 V$ Operating Temperature $0^{\circ}C \sim 70^{\circ}C$ Mounting Type Surface Mount Package / Case $16\text{-SOIC }(0.154^{\circ}, 3.90mm \text{ Width})$ Supplier Device Package 16-SO	Gain Bandwidth Product	70MHz
Voltage - Input Offset $500\mu V$ Current - Supply $6.3mA$ Current - Output / Channel $60mA$ Voltage - Supply, Single/Dual (±) $5 V \sim 36 V, \pm 2.5 V \sim 18 V$ Operating Temperature $0^{\circ}C \sim 70^{\circ}C$ Mounting TypeSurface MountPackage / Case 16-SOIC (0.154", 3.90mm Width)Supplier Device Package 16-SO	-3db Bandwidth	-
Current - Supply 6.3mA Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 5 V ~ 36 V, ±2.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SO	Current - Input Bias	600nA
Current - Output / Channel 60mA Voltage - Supply, Single/Dual (±) 5 V ~ 36 V, ±2.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SO	Voltage - Input Offset	500μV
Voltage - Supply, Single/Dual (\pm) 5 V ~ 36 V, \pm 2.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SO	Current - Supply	6.3mA
Operating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SO	Current - Output / Channel	60mA
Mounting Type Surface Mount Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SO	Voltage - Supply, Single/Dual (±)	5 V ~ 36 V, ±2.5 V ~ 18 V
Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SO	Operating Temperature	0°C ~ 70°C
Supplier Device Package 16-SO	Mounting Type	Surface Mount
	Package / Case	16-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	16-SO
		Report errors?

LT1365CS#TRPBF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LT1365CS#TRPBF Payment Methods



















LT1365CS#TRPBF Shipping Methods













If you have any question about LT1365CS#TRPBF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com