

LT6654AMPS6-1.25#TRMPBF

LT6654AMPS6-1.25#TRMPBF Information

Part Number LT6654AMPS6-1.25#TRMPBF

Manufacturer Linear Technology

Category Integrated Circuits (ICs)
PMIC - Voltage Reference

Description IC VREF SERIES 1.25V TSOT23-6

Package SOT-23-6 Thin, TSOT-23-6

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LT6654AMPS6-1.25#TRMPBF Specifications

Category Integrated Circuits (ICs) PMIC - Voltage Reference Package SOT-23-6 Thin, TSOT-23-6 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 1.25 V Voltage - Output (Max) - Current - Output 10mA Tolerance ±0.05% Temperature Coefficient 10ppm/°C Noise - 0.1Hz to 10Hz 0.8ppmp-p Noise - 10Hz to 10kHz 2ppmrms Voltage - Input 2.4 V ~ 36 V Current - Supply 600µA Current - Cathode - Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount		
Category Integrated Circuits (ICs) PMIC - Voltage Reference Package SOT-23-6 Thin, TSOT-23-6 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 1.25 V Voltage - Output (Max) - Current - Output 10mA Tolerance ±0.05% Temperature Coefficient 10ppm/°C Noise - 0.1Hz to 10Hz 0.8ppmp-p Noise - 10Hz to 10kHz 2ppmrms Voltage - Input 2.4 V ~ 36 V Current - Supply 600µA Current - Cathode - Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package TSOT-23-6	Manufacturer Part Number	LT6654AMPS6-1.25#TRMPBF
PMIC - Voltage Reference Package SOT-23-6 Thin, TSOT-23-6 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 1.25 V Voltage - Output (Max) - Current - Output 10mA Tolerance ±0.05% Temperature Coefficient 10ppm/°C Noise - 0.1Hz to 10Hz 0.8ppmp-p Noise - 10Hz to 10kHz 2ppmrms Voltage - Input 2.4 V ~ 36 V Current - Supply 600μA Current - Cathode - Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package TSOT-23-6	Manufacturer	Linear Technology
Package SOT-23-6 Thin, TSOT-23-6 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 1.25 V Voltage - Output (Max) - Current - Output 10mA Tolerance ±0.05% Temperature Coefficient 10ppm/°C Noise - 0.1Hz to 10Hz 0.8ppmp-p Noise - 10Hz to 10kHz 2ppmrms Voltage - Input 2.4 V ~ 36 V Current - Supply 600μA Current - Cathode - Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package TSOT-23-6	Category	Integrated Circuits (ICs)
Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 1.25 V Voltage - Output (Max) - Current - Output 10mA Tolerance ±0.05% Temperature Coefficient 10ppm/°C Noise - 0.1Hz to 10Hz 0.8ppmp-p Noise - 10Hz to 10kHz 2ppmrms Voltage - Input 2.4 V ~ 36 V Current - Supply 600µA Current - Cathode - Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package TSOT-23-6		PMIC - Voltage Reference
Reference TypeSeriesOutput TypeFixedVoltage - Output (Min/Fixed)1.25 VVoltage - Output (Max)-Current - Output10mATolerance±0.05%Temperature Coefficient10ppm/°CNoise - 0.1Hz to 10Hz0.8ppmp-pNoise - 10Hz to 10kHz2ppmrmsVoltage - Input2.4 V ~ 36 VCurrent - Supply600μACurrent - Cathode-Operating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6 Thin, TSOT-23-6Supplier Device PackageTSOT-23-6	Package	SOT-23-6 Thin, TSOT-23-6
Output TypeFixedVoltage - Output (Min/Fixed)1.25 VVoltage - Output (Max)-Current - Output10mATolerance±0.05%Temperature Coefficient10ppm/°CNoise - 0.1Hz to 10Hz0.8ppmp-pNoise - 10Hz to 10kHz2ppmrmsVoltage - Input2.4 V ~ 36 VCurrent - Supply600μACurrent - Cathode-Operating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6 Thin, TSOT-23-6Supplier Device PackageTSOT-23-6	Series	-
Voltage - Output (Min/Fixed) 1.25 V Voltage - Output (Max) - Current - Output 10mA Tolerance ±0.05% Temperature Coefficient 10ppm/°C Noise - 0.1Hz to 10Hz 0.8ppmp-p Noise - 10Hz to 10kHz 2ppmrms Voltage - Input 2.4 V ~ 36 V Current - Supply 600µA Current - Cathode - Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package TSOT-23-6	Reference Type	Series
Voltage - Output (Max) Current - Output 10mA Tolerance ±0.05% Temperature Coefficient 10ppm/°C Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz 2ppmrms Voltage - Input 2.4 V ~ 36 V Current - Supply 600μA Current - Cathode - Coperating Temperature Mounting Type Surface Mount Package / Case Supplier Device Package - Store A 125°C TSOT-23-6 TSOT-23-6	Output Type	Fixed
Current - Output Tolerance ±0.05% Temperature Coefficient 10ppm/°C Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz 2ppmrms Voltage - Input 2.4 V ~ 36 V Current - Supply 600µA Current - Cathode Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case Supplier Device Package 10mA ±0.05% 10pm/°C 0.8ppmp-p 0.	Voltage - Output (Min/Fixed)	1.25V
Tolerance ±0.05% Temperature Coefficient 10ppm/°C Noise - 0.1Hz to 10Hz 0.8ppmp-p Noise - 10Hz to 10kHz 2ppmrms Voltage - Input 2.4 V ~ 36 V Current - Supply 600μA Current - Cathode - Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package	Voltage - Output (Max)	-
Temperature Coefficient Noise - 0.1Hz to 10Hz 0.8ppmp-p Noise - 10Hz to 10kHz 2ppmrms Voltage - Input 2.4 V ~ 36 V Current - Supply 600μA Current - Cathode Operating Temperature Mounting Type Surface Mount Package / Case Supplier Device Package 10ppm/°C 0.8ppmp-p 2.4 V ~ 36 V 600μA	Current - Output	10mA
Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz 2ppmrms Voltage - Input 2.4 V ~ 36 V Current - Supply 600µA Current - Cathode Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package	Tolerance	$\pm 0.05\%$
Noise - 10Hz to 10kHz2ppmrmsVoltage - Input2.4 V ~ 36 VCurrent - Supply600μACurrent - Cathode-Operating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6 Thin, TSOT-23-6Supplier Device PackageTSOT-23-6	Temperature Coefficient	10ppm/°C
Voltage - Input 2.4 V ~ 36 V Current - Supply 600μA Current - Cathode - Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package	Noise - 0.1Hz to 10Hz	0.8ppmp-p
Current - Supply600μACurrent - Cathode-Operating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-6 Thin, TSOT-23-6Supplier Device PackageTSOT-23-6	Noise - 10Hz to 10kHz	2ppmrms
Current - Cathode - Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package TSOT-23-6	Voltage - Input	2.4 V ~ 36 V
Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package TSOT-23-6	Current - Supply	600μΑ
Mounting Type Surface Mount Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package TSOT-23-6	Current - Cathode	-
Package / Case SOT-23-6 Thin, TSOT-23-6 Supplier Device Package TSOT-23-6	Operating Temperature	-55°C ~ 125°C (TA)
Supplier Device Package TSOT-23-6	Mounting Type	Surface Mount
	Package / Case	SOT-23-6 Thin, TSOT-23-6
Report errors?	Supplier Device Package	TSOT-23-6
		Report errors?

LT6654AMPS6-1.25#TRMPBF Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LT6654AMPS6-1.25#TRMPBF Payment Methods



















LT6654AMPS6-1.25#TRMPBF Shipping Methods













If you have any question about LT6654AMPS6-1.25#TRMPBF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com