

LT8705AIFE#TRPBF

LT8705AIFE#TRPBF Information



For Reference Only

Part Number LT8705AIFE#TRPBF
Manufacturer Linear Technology
Category Integrated Circuits (ICs)

PMIC - Voltage Regulators - DC DC Switching

Controllers

Description IC REG CTRLR BUCK-BOOST 38TSSOP

Package 38-TFSOP (0.173", 4.40mm Width) 31 Leads,

Exposed Pad

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LT8705AIFE#TRPBF Specifications

Manufacturer Linear Technology Category Integrated Circuits (ICs) PMIC - Voltage Regulators - DC DC Switching Controllers Package 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Scries - Output Type Transistor Driver Function Step-Up/Step-Down Output Configuration Positive Topology Buck-Boost Number of Outputs 2 Output Phases 2 Voltage - Supply (Vcc/Vdd) 2.8 V ~ 80 V Frequency - Switching 100kHz ~ 400kHz Duty Cycle (Max) - Synchronous Rectifier Yes Clock Sync Yes Serial Interfaces - Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP		
Category Integrated Circuits (ICs) PMIC - Voltage Regulators - DC DC Switching Controllers Package 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Series - Output Type Transistor Driver Function Step-Up/Step-Down Output Configuration Positive Topology Buck-Boost Number of Outputs 2 Output Phases 2 Voltage - Supply (Vcc/Vdd) 2.8 V ~ 80 V Frequency - Switching 100kHz ~ 400kHz Duty Cycle (Max) - Synchronous Rectifier Yes Clock Sync Yes Serial Interfaces - Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP	Manufacturer Part Number	LT8705AIFE#TRPBF
Package 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Series - Output Type Transistor Driver Function Step-Up/Step-Down Output Configuration Positive Topology Buck-Boost Number of Outputs 2 Output Phases 2 Voltage - Supply (Vcc/Vdd) 2.8 V ~ 80 V Frequency - Switching 100kHz ~ 400kHz Duty Cycle (Max) - Synchronous Rectifier Yes Serial Interfaces - Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TSSOP	Manufacturer	Linear Technology
Package38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed PadSeries-Output TypeTransistor DriverFunctionStep-Up/Step-DownOutput ConfigurationPositiveTopologyBuck-BoostNumber of Outputs2Output Phases2Voltage - Supply (Vcc/Vdd)2.8 V ~ 80 VFrequency - Switching100kHz ~ 400kHzDuty Cycle (Max)-Synchronous RectifierYesClock SyncYesSerial Interfaces-Control FeaturesEnable, Frequency Control, Soft StartOperating Temperature-40°C ~ 125°CPackage / Case38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed PadSupplier Device Package38-TSSOP	Category	Integrated Circuits (ICs)
Series - Output Type Transistor Driver Function Step-Up/Step-Down Output Configuration Positive Topology Buck-Boost Number of Outputs 2 Output Phases 2 Voltage - Supply (Vcc/Vdd) 2.8 V ~ 80 V Frequency - Switching 100kHz ~ 400kHz Duty Cycle (Max) - Synchronous Rectifier Yes Clock Sync Yes Serial Interfaces - Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP		PMIC - Voltage Regulators - DC DC Switching Controllers
Output TypeTransistor DriverFunctionStep-Up/Step-DownOutput ConfigurationPositiveTopologyBuck-BoostNumber of Outputs2Output Phases2Voltage - Supply (Vcc/Vdd)2.8 V ~ 80 VFrequency - Switching100kHz ~ 400kHzDuty Cycle (Max)-Synchronous RectifierYesClock SyncYesSerial Interfaces-Control FeaturesEnable, Frequency Control, Soft StartOperating Temperature-40°C ~ 125°CPackage / Case38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed PadSupplier Device Package38-TSSOP	Package	38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad
Function Step-Up/Step-Down Output Configuration Positive Topology Buck-Boost Number of Outputs 2 Output Phases 2 Voltage - Supply (Vcc/Vdd) 2.8 V ~ 80 V Frequency - Switching 100kHz ~ 400kHz Duty Cycle (Max) - Synchronous Rectifier Yes Clock Sync Yes Serial Interfaces - Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP	Series	-
Output Configuration Positive Topology Buck-Boost Number of Outputs 2 Output Phases 2 Voltage - Supply (Vcc/Vdd) 2.8 V ~ 80 V Frequency - Switching 100kHz ~ 400kHz Duty Cycle (Max) - Synchronous Rectifier Yes Clock Sync Yes Serial Interfaces - Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP	Output Type	Transistor Driver
Topology Number of Outputs 2 Output Phases 2 Voltage - Supply (Vcc/Vdd) Frequency - Switching 100kHz ~ 400kHz Duty Cycle (Max) - Synchronous Rectifier Yes Clock Sync Serial Interfaces - Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP	Function	Step-Up/Step-Down
Number of Outputs Output Phases 2 Voltage - Supply (Vcc/Vdd) Frequency - Switching 100kHz ~ 400kHz Duty Cycle (Max) Synchronous Rectifier Yes Clock Sync Yes Serial Interfaces - Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package	Output Configuration	Positive
Output Phases 2 Voltage - Supply (Vcc/Vdd) 2.8 V ~ 80 V Frequency - Switching 100kHz ~ 400kHz Duty Cycle (Max) - Synchronous Rectifier Yes Clock Sync Serial Interfaces - Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP	Topology	Buck-Boost
Voltage - Supply (Vcc/Vdd) 2.8 V ~ 80 V Frequency - Switching 100kHz ~ 400kHz - Synchronous Rectifier Yes Clock Sync Serial Interfaces - Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package	Number of Outputs	2
Frequency - Switching Duty Cycle (Max) Synchronous Rectifier Yes Clock Sync Yes Serial Interfaces - Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP	Output Phases	2
Duty Cycle (Max) Synchronous Rectifier Yes Clock Sync Serial Interfaces - Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP	Voltage - Supply (Vcc/Vdd)	2.8 V ~ 80 V
Synchronous Rectifier Yes Clock Sync Yes Serial Interfaces - Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP	Frequency - Switching	100kHz ~ 400kHz
Clock Sync Serial Interfaces - Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP	Duty Cycle (Max)	-
Serial Interfaces Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP	Synchronous Rectifier	Yes
Control Features Enable, Frequency Control, Soft Start Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP	Clock Sync	Yes
Operating Temperature -40°C ~ 125°C Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP	Serial Interfaces	-
Package / Case 38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad Supplier Device Package 38-TSSOP	Control Features	Enable, Frequency Control, Soft Start
Supplier Device Package 38-TSSOP	Operating Temperature	-40°C ~ 125°C
	Package / Case	38-TFSOP (0.173", 4.40mm Width) 31 Leads, Exposed Pad
Domont owners?	Supplier Device Package	38-TSSOP
Report errors?		Report errors?

LT8705AIFE#TRPBF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LT8705AIFE#TRPBF Payment Methods



















LT8705AIFE#TRPBF Shipping Methods













If you have any question about LT8705AIFE#TRPBF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com