

LTC2261CUJ-12#PBF

LTC2261CUJ-12#PBF Information

www.unitsenteeom thattan unitsenteeom		LTC2261CUJ-12#PBF Linear Technology Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC) IC ADC 12-BIT 125MSPS 40-QFN	
	Package	40-WFQFN Exposed Pad	
For Reference Only		For the pricing/inventory/lead time, please contact	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LTC2261CUJ-12#PBF Specifications

CategoryIntegrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC)Package40-WFQFN Exposed PadSeries-Number of Bits12Sampling Rate (Per Second)125MNumber of Inputs1Input TypeDifferentialData InterfaceLVDS - Parallel, ParallelConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1Reference TypeExternal, InternalVoltage - Supply, Analog1.7 V ~ 1.9 VVoltage - Supply, Digital-Features-Operating Temperature0°C ~ 70°C		
CategoryIntegrated Circuits (ICs)Data Acquisition - Analog to Digital Converters (ADC)Package40-WFQFN Exposed PadSeries-Number of Bits12Sampling Rate (Per Second)125MNumber of Inputs1Input TypeDifferentialData Acquisition - Analog to Digital Converters (ADC)ConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1ArchitecturePielinedReference TypeExternal, InternalVoltage - Supply, Analog1.7 V ~ 1.9 VVoltage - Supply, Digital-Operating Temperature0°C ~ 70°CPackage / Case40-QFN (6s6)Mounting Type-Supplier Device Package-Mounting Type-	Manufacturer Part Number	LTC2261CUJ-12#PBF
Index Acquisition - Analog to Digital Converters (ADC)Package40-WFQFN Exposed PadSeries-Number of Bits12Sampling Rate (Per Second)12Number of Inputs1Input TypeDifferentialData InterfaceV/DS - Parallel, ParallelConfigurationS/H-ADCRatio - S/H: ADC1Number of A/D Converters1ArchitecturePielnidVoltage - Supply, Analog1.7 V ~ 1.9 VVoltage - Supply, Digital-Peatures-Operating Temperature0°C ~ 10°CPackage / Case40-WFQFN Exposed PadNumber of Arber40-UFN Exposed PadNumber of Arber-Supplier Device Package0.0 CFN CCPackage / Case40-UFN Exposed PadNuming Type-Supplier Device Package-Supplier Device Package<	Manufacturer	Linear Technology
Package40-WFQFN Exposed PadSeries-Number of Bits12Sampling Rate (Per Second)125MNumber of Inputs1Input TypeDifferentialData InterfaceLVDS - Parallel, ParallelConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1Reference TypeExternal, InternalVoltage - Supply, Analog1.7 V ~ 1.9 VVoltage - Supply, Digital-Features-Operating Temperature0°C ~ 70°CPackage / Case40-QFN (6x6)Mounting Type-	Category	Integrated Circuits (ICs)
Series-Number of Bits12Sampling Rate (Per Second)125MNumber of Inputs1Input TypeDifferentialData InterfaceLVDS - Parallel, ParallelConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedReference TypeExternal, InternalVoltage - Supply, Digital1.7 V ~ 1.9 VVoltage - Supply, Digital0°C ~ 70°CPackage / Case40-QFN (6x6)Mounting Type-		Data Acquisition - Analog to Digital Converters (ADC)
Number of Bits12Sampling Rate (Per Second)125MNumber of Inputs1Input TypeDifferentialData InterfaceLVDS - Parallel, ParallelConfigurationS/H-ADCRatio - S/H: ADC1.1Number of A/D Converters1ArchitecturePipelinedReference TypeExternal, InternalVoltage - Supply, Digital1.7 V ~ 1.9 VVoltage - Supply, Digital0°C ~ 70°CPerkange / Case40-VFN Exposed PadSupplier Device Package40-QFN (6x6)Mounting Type-	Package	40-WFQFN Exposed Pad
Sampling Rate (Per Second)125MNumber of Inputs1Input TypeDifferentialData InterfaceLVDS - Parallel, ParallelConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1ArchitecturePipelinedReference TypeExternal, InternalVoltage - Supply, Analog.7 V ~ 1.9 VVoltage - Supply, Digital-Peatures-Package / Case40-WFQFN Exposed PadSupplier Device Package40-QFN (6x6)Mounting Type-	Series	-
Number of Inputs1Input TypeDifferentialData InterfaceLVDS - Parallel, ParallelConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedReference TypeExternal, InternalVoltage - Supply, Digital1.7 V ~ 1.9 VVoltage - Supply, Digital0°C ~ 70°CPackage / Case40-WFQFN Exposed PadSupplier Device Package40-QFN (£x66)Mounting Type-	Number of Bits	12
Input TypeDifferentialData InterfaceLVDS - Parallel, ParallelConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedReference TypeExternal, InternalVoltage - Supply, Analog1.7 V ~ 1.9 VVoltage - Supply, Digital-Operating Temperature0°C ~ 70°CPackage / Case40-WFQFN Exposed PadSupplier Device Package-Mounting Type-	Sampling Rate (Per Second)	125M
Para InterfaceLVDS - Parallel, ParallelData InterfaceLVDS - Parallel, ParallelConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedReference TypeExternal, InternalVoltage - Supply, Analog1.7 V ~ 1.9 VVoltage - Supply, Digital1.7 V ~ 1.9 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case40-WFQFN Exposed PadSupplier Device Package40-QFN (6x6)Mounting Type-	Number of Inputs	1
ConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedReference TypeExternal, InternalVoltage - Supply, Analog1.7 V ~ 1.9 VVoltage - Supply, Digital1.7 V ~ 1.9 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case40-WFQFN Exposed PadMounting Type-	Input Type	Differential
Ratio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedArchitectureExternal, InternalKeference TypeExternal, InternalVoltage - Supply, Analog1.7 V ~ 1.9 VVoltage - Supply, Digital1.7 V ~ 1.9 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case40-WFQFN Exposed PadSupplier Device Package-Mounting Type-	Data Interface	LVDS - Parallel, Parallel
Number of A/D Converters1ArchitecturePipelinedArchitecturePipelinedReference TypeExternal, InternalVoltage - Supply, Analog1.7 V ~ 1.9 VVoltage - Supply, Digital1.7 V ~ 1.9 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case40-WFQFN Exposed PadSupplier Device Package-Mounting Type-	Configuration	S/H-ADC
ArchitecturePipelinedReference TypeExternal, InternalVoltage - Supply, Analog1.7 V ~ 1.9 VVoltage - Supply, Digital1.7 V ~ 1.9 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case40-WFQFN Exposed PadSupplier Device Package40-QFN (6x6)Mounting Type-	Ratio - S/H:ADC	1:1
Reference TypeExternal, InternalVoltage - Supply, Analog1.7 V ~ 1.9 VVoltage - Supply, Digital1.7 V ~ 1.9 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case40-WFQFN Exposed PadSupplier Device Package40-QFN (6x6)Mounting Type-	Number of A/D Converters	1
Voltage - Supply, Analog1.7 V ~ 1.9 VVoltage - Supply, Digital1.7 V ~ 1.9 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case40-WFQFN Exposed PadSupplier Device Package40-QFN (6x6)Mounting Type-	Architecture	Pipelined
Voltage - Supply, Digital1.7 V ~ 1.9 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case40-WFQFN Exposed PadSupplier Device Package40-QFN (6x6)Mounting Type-	Reference Type	External, Internal
Features-Operating Temperature0°C ~ 70°CPackage / Case40-WFQFN Exposed PadSupplier Device Package40-QFN (6x6)Mounting Type-	Voltage - Supply, Analog	1.7 V ~ 1.9 V
Operating Temperature0°C ~ 70°CPackage / Case40-WFQFN Exposed PadSupplier Device Package40-QFN (6x6)Mounting Type-	Voltage - Supply, Digital	1.7 V ~ 1.9 V
Package / Case40-WFQFN Exposed PadSupplier Device Package40-QFN (6x6)Mounting Type-	Features	-
Supplier Device Package40-QFN (6x6)Mounting Type-	Operating Temperature	$0^{\circ}C \sim 70^{\circ}C$
Mounting Type -	Package / Case	40-WFQFN Exposed Pad
	Supplier Device Package	40-QFN (6x6)
Report errors?	Mounting Type	-
		Report errors?

LTC2261CUJ-12#PBF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

LTC2261CUJ-12#PBF Payment Methods



If you have any question about LTC2261CUJ-12#PBF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com