

LTC2312HTS8-14#TRMPBF

LTC2312HTS8-14#TRMPBF Information



For Reference Only

Part Number LTC2312HTS8-14#TRMPBF

Manufacturer Linear Technology

Category Integrated Circuits (ICs)

Data Acquisition - Analog to Digital Converters

(ADC)

Description IC ADC 14BIT 500KSPS TSOT23-8

Package SOT-23-8 Thin, TSOT-23-8

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LTC2312HTS8-14#TRMPBF Specifications

Manufacturer Part Number LTC2312HTS8-14#TRMPBF Manufacturer Linear Technology Category Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC) Package SOT-23-8 Thin, TSOT-23-8 Series - Number of Bits 14 Sampling Rate (Per Second) 500k Number of Inputs 1 Input Type Single Ended Data Interface SPI Configuration S/H-ADC Ratio - S/H:ADC 1:1 Number of A/D Converters 1 Architecture SAR Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 3.6 V, 5V Voltage - Supply, Digital 2.7 V ~ 3.6 V, 5V Features - Operating Temperature 40°C ~ 125°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package TSOT-23-8 Mounting Type Report errors?		
Category Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC) Package SOT-23-8 Thin, TSOT-23-8 Series - Number of Bits 14 Sampling Rate (Per Second) 500k Number of Inputs 1 Input Type Single Ended Data Interface SPI Configuration S/H-ADC Ratio - S/H:ADC 1:1 Number of A/D Converters 1 Architecture SAR Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 3.6 V, 5V Voltage - Supply, Digital 2.7 V ~ 3.6 V, 5V Features - Operating Temperature -40°C ~ 125°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package TSOT-23-8 Mounting Type -	Manufacturer Part Number	LTC2312HTS8-14#TRMPBF
Data Acquisition - Analog to Digital Converters (ADC) Package SOT-23-8 Thin, TSOT-23-8 Series - Number of Bits 14 Sampling Rate (Per Second) 500k Number of Inputs 1 Input Type Single Ended Data Interface SPI Configuration S/H-ADC Ratio - S/H:ADC 1:1 Number of A/D Converters 1 Architecture SAR Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 3.6 V, 5V Voltage - Supply, Digital 2.7 V ~ 3.6 V, 5V Features - Operating Temperature -40°C ~ 125°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package TSOT-23-8 Mounting Type -	Manufacturer	Linear Technology
Package SOT-23-8 Thin, TSOT-23-8 Series - Number of Bits 14 Sampling Rate (Per Second) 500k Number of Inputs 1 Input Type Single Ended Data Interface SPI Configuration S/H-ADC Ratio - S/H:ADC 1:1 Number of A/D Converters 1 Architecture SAR Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 3.6 V, 5V Voltage - Supply, Digital 2.7 V ~ 3.6 V, 5V Features - Operating Temperature -40°C ~ 125°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package TSOT-23-8 Mounting Type -	Category	Integrated Circuits (ICs)
Series - Number of Bits 14 Sampling Rate (Per Second) 500k Number of Inputs 1 Input Type Single Ended Data Interface SPI Configuration S/H-ADC Ratio - S/H:ADC 1:1 Number of A/D Converters 1 Architecture SAR Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 3.6 V, 5V Voltage - Supply, Digital 2.7 V ~ 3.6 V, 5V Features - Operating Temperature -40°C ~ 125°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package TSOT-23-8 Mounting Type -		Data Acquisition - Analog to Digital Converters (ADC)
Number of Bits14Sampling Rate (Per Second)500kNumber of Inputs1Input TypeSingle EndedData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 V, 5VVoltage - Supply, Digital2.7 V ~ 3.6 V, 5VFeatures-Operating Temperature-40°C ~ 125°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Package	SOT-23-8 Thin, TSOT-23-8
Sampling Rate (Per Second)500kNumber of Inputs1Input TypeSingle EndedData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 V, 5 VVoltage - Supply, Digital2.7 V ~ 3.6 V, 5 VFeatures-Operating Temperature-40°C ~ 125°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Series	-
Number of Inputs 1 Input Type Single Ended Data Interface SPI Configuration S/H-ADC Ratio - S/H:ADC 1:1 Number of A/D Converters 1 Architecture SAR Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 3.6 V, 5V Voltage - Supply, Digital 2.7 V ~ 3.6 V, 5V Features - Operating Temperature -40°C ~ 125°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package TSOT-23-8 Mounting Type -	Number of Bits	14
Input Type Data Interface SPI Configuration S/H-ADC Ratio - S/H:ADC 1:1 Number of A/D Converters 1 Architecture SAR Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 3.6 V, 5V Voltage - Supply, Digital 2.7 V ~ 3.6 V, 5V Features Operating Temperature -40°C ~ 125°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package Mounting Type SHEADC SHEADC Italian SHEADC 1:1 1.1 Architecture SAR Internal 2.7 V ~ 3.6 V, 5V Voltage - Supply, Digital 2.7 V ~ 3.6 V, 5V SUPPLIED SUPPL	Sampling Rate (Per Second)	500k
Data InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 V, 5VVoltage - Supply, Digital2.7 V ~ 3.6 V, 5VFeatures-Operating Temperature-40°C ~ 125°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Number of Inputs	1
Configuration Ratio - S/H:ADC 1:1 Number of A/D Converters 1 Architecture SAR Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 3.6 V, 5V Voltage - Supply, Digital 2.7 V ~ 3.6 V, 5V Features Operating Temperature -40°C ~ 125°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package Mounting Type - SAR 1 Architecture SAR Architecture SAR Architecture SAR Architecture SAR Architecture SAR Architecture SAR SAR Internal -2.7 V ~ 3.6 V, 5V -3.6 V, 5V -4.0°C ~ 125°C	Input Type	Single Ended
Ratio - S/H:ADC Number of A/D Converters 1 Architecture SAR Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 3.6 V, 5V Voltage - Supply, Digital 2.7 V ~ 3.6 V, 5V Features - Operating Temperature -40°C ~ 125°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package Mounting Type - 1:1 Architecture SAR Internal 2.7 V ~ 3.6 V, 5V - **Contact of the package of the packag	Data Interface	SPI
Number of A/D Converters Architecture SAR Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 3.6 V, 5V Voltage - Supply, Digital 2.7 V ~ 3.6 V, 5V Features - Operating Temperature -40°C ~ 125°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package Mounting Type - 1 Architecture SAR Internal 2.7 V ~ 3.6 V, 5V 2.7 V ~ 3.6 V, 5V - TSOT-23-8 Supplier Device Package TSOT-23-8	Configuration	S/H-ADC
Architecture Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 3.6 V, 5V Voltage - Supply, Digital 2.7 V ~ 3.6 V, 5V Features - Operating Temperature Package / Case SOT-23-8 Thin, TSOT-23-8 Mounting Type - SAR Internal 2.7 V ~ 3.6 V, 5V - SOT-23-8 Mounting Type - SOT-23-8 Fackage SOT-23-8 Mounting Type - SOT-23-8	Ratio - S/H:ADC	1:1
Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 3.6 V, 5V Voltage - Supply, Digital 2.7 V ~ 3.6 V, 5V Features - Operating Temperature -40°C ~ 125°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package TSOT-23-8 Mounting Type -	Number of A/D Converters	1
Voltage - Supply, Analog 2.7 V \sim 3.6 V, 5V Voltage - Supply, Digital 2.7 V \sim 3.6 V, 5V Features - Operating Temperature -40°C \sim 125°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package TSOT-23-8 Mounting Type -	Architecture	SAR
Voltage - Supply, Digital $2.7 \text{ V} \sim 3.6 \text{ V}$, 5V Features - Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package TSOT-23-8 Mounting Type -	Reference Type	Internal
Features - Operating Temperature -40°C ~ 125°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package TSOT-23-8 Mounting Type -	Voltage - Supply, Analog	2.7 V ~ 3.6 V, 5V
Operating Temperature -40°C ~ 125°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package TSOT-23-8 Mounting Type -	Voltage - Supply, Digital	2.7 V ~ 3.6 V, 5V
Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package TSOT-23-8 Mounting Type -	Features	-
Supplier Device Package TSOT-23-8 Mounting Type -	Operating Temperature	-40°C ~ 125°C
Mounting Type -	Package / Case	SOT-23-8 Thin, TSOT-23-8
2 12	Supplier Device Package	TSOT-23-8
Report errors?	Mounting Type	-
		Report errors?

LTC2312HTS8-14#TRMPBF Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LTC2312HTS8-14#TRMPBF Payment Methods

































If you have any question about LTC2312HTS8-14#TRMPBF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com