

LTC2376CMS-18#PBF

LTC2376CMS-18#PBF Information

www.chadd.com		LTC2376CMS-18#PBF Linear Technology Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC)	
	Description	IC ADC 18BIT 250KSPS 16-MSOP	- SNP 44
	Package	16-TFSOP (0.118", 3.00mm Width)	- 国際登場
For Reference Only		For the pricing/inventory/lead time, please contact	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LTC2376CMS-18#PBF Specifications

CategoryIntegrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC)Package16-TFSOP (0.118", 3.00mm Width)Series-Number of Bits18Sampling Rate (Per Second)250kNumber of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.375 V ~ 2.625 VVoltage - Supply, Digital-Pertures-Operating Temperature0°C ~ 70°C		
CategoryIntegrated Circuis (ICs)Data Acquisition - Analog to Digital Converters (ADC)Package16-TFSOP (0.118", 3.00mm Width)Series-Number of Bits18Sampling Rate (Per Second)250kNumber of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCNumber of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.375 V ~ 2.625 VVoltage - Supply, Digital2.375 V ~ 2.625 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case16-MSOPMounting Type-Supplier Device Package16-MSOPMounting Type-	Manufacturer Part Number	LTC2376CMS-18#PBF
Index Acquisition - Analog to Digital Converters (ADC)Package16-TFSOP (0.118", 3.00mm Width)Stries-Number of Bits18Sampling Rate (Per Second)250kNumber of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H: ADC1Number of A/D Converters1ArchitectureSARReference Type2.375 V - 2.625 VVoltage - Supply, Digital2.375 V - 2.625 VVoltage - Supply, Digital-Pertures-Operating Temperature0°C - 70°CPackage / Case16-MSOP (0.118", 3.00mm Width)Auting Type-Supplier Device Package-Munting Type-Supplier Device Package-Supplier Device Package-<	Manufacturer	Linear Technology
Package16-TFSOP (0.118", 3.00mm Width)Series-Number of Bits18Sampling Rate (Per Second)250kNumber of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1Reference TypeExternalVoltage - Supply, Analog2.375 V ~ 2.625 VVoltage - Supply, Digital-Peakage / Case16-TFSOP (0.118", 3.00mm Width)Supplier Device Package16-MSOPMounting Type-	Category	Integrated Circuits (ICs)
Series-Number of Bits18Sampling Rate (Per Second)250kNumber of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Digital2.375 V ~ 2.625 VVoltage - Supply, Digital-Operating Temperature0°C ~ 70°CPackage / Case16-MSOPMounting Type-		Data Acquisition - Analog to Digital Converters (ADC)
Number of Bits18Sampling Rate (Per Second)250kNumber of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H: ADC1.1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.375 V ~ 2.625 VVoltage - Supply, Digital0°C ~ 70°CPeatures6°C ~ 70°CPackage / Case16-MSOPMounting Type-Supplier Device Package6.Supplier Device Package-Supplier Device P	Package	16-TFSOP (0.118", 3.00mm Width)
Sampling Rate (Per Second)250kNumber of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.375 V ~ 2.625 VVoltage - Supply, Digital-Package / Case0°C ~ 70°CSupplier Device Package16-MSOP (0.118", 3.00mm Width)Mounting Type-	Series	-
Number of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Digital2.375 V ~ 2.625 VVoltage - Supply, Digital-Operating Temperature0°C ~ 70°CPackage / Case16-TFSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-	Number of Bits	18
Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.375 V ~ 2.625 VVoltage - Supply, Digital-Operating Temperature0°C ~ 70°CPackage / Case16-MSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-	Sampling Rate (Per Second)	250k
Part of the constraint of the co	Number of Inputs	1
ConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.375 V ~ 2.625 VVoltage - Supply, Digital:375 V ~ 2.625 VPeatures-Operating Temperature0°C ~ 70°CPackage / Case16-TFSOP (0.118", 3.00mm Width)Mounting Type:	Input Type	Differential
Ratio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.375 V ~ 2.625 VVoltage - Supply, Digital2.375 V ~ 2.625 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case16-TFSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-	Data Interface	SPI
Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.375 V ~ 2.625 VVoltage - Supply, Digital2.375 V ~ 2.625 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case16-TFSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-	Configuration	S/H-ADC
ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.375 V ~ 2.625 VVoltage - Supply, Digital2.375 V ~ 2.625 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case16-TFSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-	Ratio - S/H:ADC	1:1
Reference TypeExternalVoltage - Supply, Analog2.375 V ~ 2.625 VVoltage - Supply, Digital2.375 V ~ 2.625 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case16-TFSOP (0.118", 3.00mm Width)Supplier Device Package16-MSOPMounting Type-	Number of A/D Converters	1
Voltage - Supply, Analog2.375 V ~ 2.625 VVoltage - Supply, Digital2.375 V ~ 2.625 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case16-TFSOP (0.118", 3.00mm Width)Supplier Device Package16-MSOPMounting Type-	Architecture	SAR
Voltage - Supply, Digital2.375 V ~ 2.625 VFeatures-Operating Temperature0°C ~ 70°CPackage / Case16-TFSOP (0.118", 3.00mm Width)Supplier Device Package16-MSOPMounting Type-	Reference Type	External
Features-Operating Temperature0°C ~ 70°CPackage / Case16-TFSOP (0.118", 3.00mm Width)Supplier Device Package16-MSOPMounting Type-	Voltage - Supply, Analog	2.375 V ~ 2.625 V
Operating Temperature0°C ~ 70°CPackage / Case16-TFSOP (0.118", 3.00mm Width)Supplier Device Package16-MSOPMounting Type-	Voltage - Supply, Digital	2.375 V ~ 2.625 V
Package / Case16-TFSOP (0.118", 3.00mm Width)Supplier Device Package16-MSOPMounting Type-	Features	-
Supplier Device Package16-MSOPMounting Type-	Operating Temperature	0° C ~ 70° C
Mounting Type -	Package / Case	16-TFSOP (0.118", 3.00mm Width)
	Supplier Device Package	16-MSOP
Report errors?	Mounting Type	-
		Report errors?

LTC2376CMS-18#PBF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

LTC2376CMS-18#PBF Payment Methods





If you have any question about LTC2376CMS-18#PBF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com