

LTL2R3EW3KS

LTL2R3EW3KS Information

	Heisener.com	Part Number Manufacturer Category Description Package	LTL2R3EW3KS Lite-On Inc. Optoelectronics LED Indication - Discrete LAMP 5MM RED 624NM CLR Radial For the pricing/inventory/lead time, please contact	
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LTL2R3EW3KS Specifications

ManufacturerLite-On Inc.CategoryOptoelectronicsLED Indication - DiscretePackageRadialSeries-ColorRedColorfiguration-ColorfigurationColorlessLens ColorColorlessMillicandela Rating5350mcdVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle30°Mounting TypeFhrough HoleWavelength - Peak622nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm		
CategoryOptoelectronicsLED Indication - DiscretePackageRadialSeries-ColorRedConfiguration-ConfigurationColorlessLens ColorClearMillicandela Rating5350mcdVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle30°Munting Type1frough HoleWavelength - Peaka627nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Manufacturer Part Number	LTL2R3EW3KS
LED Indication - DiscretePackageRadialSeries-ColorRedConfiguration-Lens ColorColorlessLens TansparencyClearMillicandela Rating5350mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 4.80mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant622nmSeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Manufacturer	Lite-On Inc.
PackageRadialSeries-ColorRedConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela RatingS350mcd Tong Tong Tong Tong Tong Tong Tong Tong	Category	Optoelectronics
Series-Series-ColorRedConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating5350mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 4.80mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant622nmVackage / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm		LED Indication - Discrete
ColorRedConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating5350mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 4.80mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant622nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Package	Radial
Configuration-Lens ColorColorlessLens TransparencyClearMillicandela Rating5350mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 4.80mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant622nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating5350mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 4.80mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mACurrent - Test30°Mounting TypeThrough HoleWavelength - Dominant622nmVerkeng / CaseRadialSupplier Device PackageT-1 3/4Supplier Device PackageT-1 3/4Height (Max)12.80mm	Color	Red
Lens TransparencyClearMillicandela Rating5350mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 4.80mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mACurrent - Test30°Viewing Angle30°Mounting Type622nmWavelength - Dominant622nmVavelength - Peak627nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension12.80mm	Configuration	-
Millicandela Rating5350mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 4.80mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant622nmWavelength - Peak627nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Lens Color	Colorless
Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 4.80mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant622nmWavelength - Peak627nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant622nmWavelength - Peak627nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Millicandela Rating	5350mcd
Current - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant622nmWavelength - Peak627nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4), 4.80mm
Viewing Angle30°Mounting TypeThrough HoleWavelength - Dominant622nmWavelength - Peak627nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Voltage - Forward (Vf) (Typ)	2.1V
Mounting TypeThrough HoleWavelength - Dominant622nmWavelength - Peak627nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Current - Test	20mA
Wavelength - Dominant622nmWavelength - Peak627nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Viewing Angle	30°
Wavelength - Peak627nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Mounting Type	Through Hole
Features-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Wavelength - Dominant	622nm
Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Wavelength - Peak	627nm
Supplier Device PackageT-1 3/4Size / Dimension-Height (Max)12.80mm	Features	-
Size / Dimension - Height (Max) 12.80mm	Package / Case	Radial
Height (Max) 12.80mm	Supplier Device Package	T-1 3/4
	Size / Dimension	-
Report errors?	Height (Max)	12.80mm
		Report errors?

LTL2R3EW3KS Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

LTL2R3EW3KS Payment Methods



LTL2R3EW3KS Shipping Methods



If you have any question about LTL2R3EW3KS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com