

LVSP0100VXL

LVSP0100VXL Information

	Part Number	LVSP0100VXL
www.heisener.o	Manufacturer	Littelfuse Inc.
	Category	Circuit Protection Electrical, Specialty Fuses
	Description	FUSE CRTRDGE 100A 600VAC CYLINDR
	Package	Cylindrical, Blade Terminal (Bolt)
		For the pricing/inventory/lead time, please contact
		us
For Reference Only		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LVSP0100VXL Specifications

Manufacturer Part NumberLVSP0100VXLManufacturerLittelfuse Inc.CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LVSPFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsTVSS ProtectionFatures-Class-ApprovalsUROperating Type200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension-Store / Dimension-Store / Case-Size / Dimension-Size / DimensionSite / DimensionSize / DimensionSite / DimensionSize / DimensionSite / Dimension		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LVSPFuse TypeCatridgeCurrent Rating100AVoltage Rating - AC600VVoltage Rating - DCSiowApplicationsStorectionApplications-Features-ApprovalsUROperating Temperature-ApprovalsURApprovalsSiowAApprovals-Aparting Temperature-Auting Type-Auting TypeBolt MountAutoning TypeSiowSize / DimensionSile" Diax 3.50" L(20.73mm x 91.19mm)	Manufacturer Part Number	LVSP0100VXL
Filectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LVSPFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsTVSS ProtectionFeatures-Class-Operating TemperatureSlowAOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.816" Dia x 3.590" L (20.73mm x 91.19mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LVSPFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsTVSS ProtectionFeatures-Class-ApprovalsUROperating Temperature-Preaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.816" Diax 3.590" L(20.73mm x 91.19mm)	Category	Circuit Protection
SeriesPOWR-GARD? LVSPFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsTVSS ProtectionFeatures-Class-ApprovalsUROperating Temperature200kABreaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical Blade Terminal (Bolt)Size / Dimension0.816" Dia x 3.590" L (20.73mm x 91.19mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeFuse Type100ACurrent Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsTVSS ProtectionFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical Balde Terminal (Bolt)Size / Dimension0.816" Dia x 3.590" L (20.73mm x 91.19mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating100AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsTVSS ProtectionFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.816" Dia x 3.590" L (20.73mm x 91.19mm)	Series	POWR-GARD? LVSP
Voltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsTVSS ProtectionFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountPackage / CaseSlowSize / Dimension0.816"Dia x 3.590"L (20.73mm x 91.19mm)	Fuse Type	Cartridge
Voltage Rating - DC-Response TimeSlowApplicationsTVSS ProtectionFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.816" Dia x 3.590" L (20.73mm x 91.19mm)	Current Rating	100A
Response TimeSlowApplicationsTVSS ProtectionFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.816" Dia x 3.590" L (20.73mm x 91.19mm)	Voltage Rating - AC	600V
ApplicationsTVSS ProtectionFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical Blade Terminal (Bolt)Size / Dimension0.816" Diax 3.590" L (20.73mm x 91.19mm)	Voltage Rating - DC	-
Fratures-Features-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.816" Dia x 3.590" L (20.73mm x 91.19mm)	Response Time	Slow
Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.816" Dia x 3.590" L (20.73mm x 91.19mm)	Applications	TVSS Protection
ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.816" Dia x 3.590" L (20.73mm x 91.19mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.816" Dia x 3.590" L (20.73mm x 91.19mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.816" Dia x 3.590" L (20.73mm x 91.19mm)	Approvals	UR
Mounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.816" Dia x 3.590" L (20.73mm x 91.19mm)	Operating Temperature	-
Package / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.816" Dia x 3.590" L (20.73mm x 91.19mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.816" Dia x 3.590" L (20.73mm x 91.19mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors'	Size / Dimension	0.816" Dia x 3.590" L (20.73mm x 91.19mm)
		Report errors?

LVSP0100VXL Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

LVSP0100VXL Payment Methods



LVSP0100VXL Shipping Methods



If you have any question about LVSP0100VXL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com