

LXC30-0350S Information

Part Number LXC30-0350S

Manufacturer Excelsys Technologies Ltd

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CC AC/DC 42-85V 350MA

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LXC30-0350S Specifications

Manufacturer Part Number LXC30-0350S Manufacturer Excelsys Technologies Ltd Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LXC30 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output (Max) 350mA Power (Watts) 30W Voltage - Isolation 3.75kV (3750V) Dimming - Features OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 6.88" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)		
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LXC30 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Output (Max) 264VAC Voltage - Output (Max) 350mA Power (Watts) 30W Voltage - Isolation 3.75kV (3750V) Dimming - Features OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)	Manufacturer Part Number	LXC30-0350S
Package - Series LXC30 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 42 ~ 85 V Current - Output (Max) 350mA Power (Watts) 30W Voltage - Isolation 3.75kV (3750V) Dimming - Features OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)	Manufacturer	Excelsys Technologies Ltd
Package - Series LXC30 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 42 ~ 85 V Current - Output (Max) 350mA Power (Watts) 30W Voltage - Isolation 3.75kV (3750V) Dimming - Features OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)	Category	Power Supplies - External/Internal (Off-Board)
Series LXC30 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 42 ~ 85 V Current - Output (Max) 350mA Power (Watts) 30W Voltage - Isolation 3.75kV (3750V) Dimming - Features OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)		LED Drivers
Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 42 ~ 85 V Current - Output (Max) 350mA Power (Watts) 30W Voltage - Isolation 3.75kV (3750V) Dimming - Features OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)	Package	-
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Output (Max) 264VAC Voltage - Output (Max) 350mA Power (Watts) 30W Voltage - Isolation 3.75kV (3750V) Dimming - Features OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)	Series	LXC30
Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 42 ~ 85 V Current - Output (Max) 350mA Power (Watts) 30W Voltage - Isolation 3.75kV (3750V) Dimming - Features OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)	Туре	Constant Current
Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 42 ~ 85 V Current - Output (Max) 350mA Power (Watts) 30W Voltage - Isolation 3.75kV (3750V) Dimming - Features OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)	Topology	AC DC Converter
Voltage - Input (Max) 264VAC Voltage - Output $42 \sim 85 \text{ V}$ Current - Output (Max) 350mA Power (Watts) 30W Voltage - Isolation $3.75\text{kV} (3750\text{V})$ Dimming-Features $O\text{VP}$, SCPRatings $IP67$ Operating Temperature $-35^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Efficiency 87% Termination StyleWire LeadsSize / Dimension $6.38^{\circ}\text{ L x } 1.67^{\circ}\text{ W x } 1.36^{\circ}\text{ H } (162.0\text{mm x } 42.5\text{mm x } 34.5\text{mm})$	Number of Outputs	1
Voltage - Output 42 ~ 85 V Current - Output (Max) 350mA Power (Watts) 30W Voltage - Isolation 3.75kV (3750V) Dimming - Features OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)	Voltage - Input (Min)	90VAC
Current - Output (Max) 350mA Power (Watts) 30W Voltage - Isolation 3.75kV (3750V) Dimming - Features OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)	Voltage - Input (Max)	264VAC
Power (Watts) $30W$ Voltage - Isolation $3.75kV (3750V)$ Dimming-Features OVP, SCP Ratings $IP67$ Operating Temperature $-35^{\circ}C \sim 60^{\circ}C$ Efficiency 87% Termination StyleWire LeadsSize / Dimension $6.38'' L \times 1.67'' W \times 1.36'' H (162.0mm \times 42.5mm \times 34.5mm)$	Voltage - Output	42 ~ 85 V
Voltage - Isolation $3.75kV (3750V)$ Dimming-FeaturesOVP, SCPRatingsIP67Operating Temperature $-35^{\circ}C \sim 60^{\circ}C$ Efficiency 87% Termination StyleWire LeadsSize / Dimension 6.38 " L x 1.67 " W x 1.36 " H $(162.0 \text{mm x } 42.5 \text{mm x } 34.5 \text{mm})$	Current - Output (Max)	350mA
Dimming Features OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension	Power (Watts)	30W
FeaturesOVP, SCPRatingsIP67Operating Temperature -35° C $\sim 60^{\circ}$ CEfficiency 87% Termination StyleWire LeadsSize / Dimension 6.38 " L x 1.67 " W x 1.36 " H (162.0 mm x 42.5 mm x 34.5 mm)	Voltage - Isolation	3.75kV (3750V)
RatingsIP67Operating Temperature $-35^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Efficiency 87% Termination StyleWire LeadsSize / Dimension $6.38''$ L x $1.67''$ W x $1.36''$ H $(162.0\text{mm x } 42.5\text{mm x } 34.5\text{mm})$	Dimming	-
Operating Temperature -35°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)	Features	OVP, SCP
Efficiency 87% Termination Style Wire Leads Size / Dimension 6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)	Ratings	IP67
Termination Style Wire Leads Size / Dimension 6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)	Operating Temperature	-35°C ~ 60°C
Size / Dimension 6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)	Efficiency	87%
	Termination Style	Wire Leads
Report errors?	Size / Dimension	6.38" L x 1.67" W x 1.36" H (162.0mm x 42.5mm x 34.5mm)
		Report errors?

LXC30-0350S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LXC30-0350S Payment Methods



















LXC30-0350S Shipping Methods













If you have any question about LXC30-0350S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com