



## **LXC40-2220SW Information**

Heisener.com

Part Number LXC40-2220SW

Manufacturer Excelsys Technologies Ltd

Category Power Supplies - External/Internal (Off-Board)

**LED Drivers** 

**Description** LED DRIVER CC AC/DC 6-16V 2.22A

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **LXC40-2220SW Specifications**

Manufacturer Part Number         LXC40-2220SW           Manufacturer         Excelsys Technologies Ltd           Category         Power Supplies - External/Internal (Off-Board)           LED Drivers           Package         -           Series         LXC40           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         6 ~ 16 V           Current - Output (Max)         2.22A           Power (Watts)         40W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OVP, SCP           Ratings         IP66           Operating Temperature         -20°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)			
Category         Power Supplies - External/Internal (Off-Board)           LED Drivers           Package         -           Series         LXC40           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         6 ~ 16 V           Current - Output (Max)         2.22A           Power (Watts)         40W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OVP, SCP           Ratings         IP66           Operating Temperature         -20°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Manufacturer Part Number	LXC40-2220SW	
Package         -           Series         LXC40           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Output (Max)         305VAC           Voltage - Output (Max)         2.22A           Power (Watts)         40W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OVP, SCP           Ratings         IP66           Operating Temperature         -20°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Manufacturer	Excelsys Technologies Ltd	
Package         -           Series         LXC40           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         6 ~ 16 V           Current - Output (Max)         2.22A           Power (Watts)         40W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OVP, SCP           Ratings         IP66           Operating Temperature         -20°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series         LXC40           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         6 ~ 16 V           Current - Output (Max)         2.22A           Power (Watts)         40W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OVP, SCP           Ratings         IP66           Operating Temperature         -20°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)		LED Drivers	
Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         6 ~ 16 V           Current - Output (Max)         2.22A           Power (Watts)         40W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OVP, SCP           Ratings         IP66           Operating Temperature         -20°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Package	-	
Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90V AC           Voltage - Input (Max)         305 V AC           Voltage - Output         6 ~ 16 V           Current - Output (Max)         2.22 A           Power (Watts)         40 W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OVP, SCP           Ratings         IP66           Operating Temperature         -20°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Series	LXC40	
Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         6 ~ 16 V           Current - Output (Max)         2.22A           Power (Watts)         40W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OVP, SCP           Ratings         IP66           Operating Temperature         -20°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Туре	Constant Current	
Voltage - Input (Min)       90VAC         Voltage - Input (Max)       305VAC         Voltage - Output       6 ~ 16 V         Current - Output (Max)       2.22A         Power (Watts)       40W         Voltage - Isolation       3kV (3000V)         Dimming       -         Features       OVP, SCP         Ratings       IP66         Operating Temperature       -20°C ~ 60°C         Efficiency       85%         Termination Style       Wire Leads         Size / Dimension       3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Topology	AC DC Converter	
Voltage - Input (Max)         305VAC           Voltage - Output         6 ~ 16 V           Current - Output (Max)         2.22A           Power (Watts)         40W           Voltage - Isolation         3kV (3000V)           Dimming         -           Features         OVP, SCP           Ratings         IP66           Operating Temperature         -20°C ~ 60°C           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Number of Outputs	1	
Voltage - Output       6 ~ 16 V         Current - Output (Max)       2.22A         Power (Watts)       40W         Voltage - Isolation       3kV (3000V)         Dimming       -         Features       OVP, SCP         Ratings       IP66         Operating Temperature       -20°C ~ 60°C         Efficiency       85%         Termination Style       Wire Leads         Size / Dimension       3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Voltage - Input (Min)	90VAC	
Current - Output (Max)       2.22A         Power (Watts)       40W         Voltage - Isolation       3kV (3000V)         Dimming       -         Features       OVP, SCP         Ratings       IP66         Operating Temperature       -20°C ~ 60°C         Efficiency       85%         Termination Style       Wire Leads         Size / Dimension       3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Voltage - Input (Max)	305VAC	
Power (Watts) 40W  Voltage - Isolation 3kV (3000V)  Dimming -  Features OVP, SCP  Ratings IP66  Operating Temperature -20°C ~ 60°C  Efficiency 85%  Termination Style Wire Leads  Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Voltage - Output	6 ~ 16 V	
Voltage - Isolation 3kV (3000V)  Dimming -  Features OVP, SCP  Ratings IP66 Operating Temperature -20°C ~ 60°C  Efficiency 85%  Termination Style Wire Leads  Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Current - Output (Max)	2.22A	
Dimming Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 85% Termination Style Wire Leads Size / Dimension	Power (Watts)	40W	
Features OVP, SCP  Ratings IP66 Operating Temperature -20°C ~ 60°C  Efficiency 85% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Voltage - Isolation	3kV (3000V)	
Ratings IP66 Operating Temperature $-20^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Efficiency 85% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Dimming	-	
Operating Temperature  -20°C ~ 60°C  Efficiency  85%  Termination Style  Wire Leads  Size / Dimension  3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Features	OVP, SCP	
Efficiency 85%  Termination Style Wire Leads  Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Ratings	IP66	
Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Operating Temperature	-20°C ~ 60°C	
Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Efficiency	85%	
	Termination Style	Wire Leads	
Report errors?	Size / Dimension	3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	
			Report errors?

#### **LXC40-2220SW Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **LXC40-2220SW Payment Methods**





















### LXC40-2220SW Shipping Methods













If you have any question about LXC40-2220SW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com