



LXD150-1050SH Information



For Reference Only

Part Number LXD150-1050SH

Manufacturer Excelsys Technologies Ltd

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CC AC/DC 71-142V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LXD150-1050SH Specifications

Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LXD150H Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 249VAC Voltage - Input (Max) 528VAC Voltage - Output 71 ~ 142 V Current - Output (Max) 1.05A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C			
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LXD150H Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 249VAC Voltage - Input (Max) 528VAC Voltage - Output 71 ~ 142 V Current - Output (Max) 1.05A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Manufacturer Part Number	LXD150-1050SH	
LED Drivers Package - Series LXD150H Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 249VAC Voltage - Output (Max) 528VAC Voltage - Output (Max) 1.05A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Manufacturer	Excelsys Technologies Ltd	
Package - Series LXD150H Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 249VAC Voltage - Input (Max) 528VAC Voltage - Output 71 ~ 142 V Current - Output (Max) 1.05A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series LXD150H Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 249VAC Voltage - Input (Max) 528VAC Voltage - Output 71 ~ 142 V Current - Output (Max) 1.05A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)		LED Drivers	
Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 249VAC Voltage - Input (Max) 528VAC Voltage - Output 71 ~ 142 V Current - Output (Max) 1.05A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Package	-	
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 249VAC Voltage - Input (Max) 528VAC Voltage - Output 71 ~ 142 V Current - Output (Max) 1.05A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Series	LXD150H	
Number of Outputs 1 Voltage - Input (Min) 249VAC Voltage - Input (Max) 528VAC Voltage - Output 71 ~ 142 V Current - Output (Max) 1.05A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Туре	Constant Current	
Voltage - Input (Min) 249VAC Voltage - Output 71 ~ 142 V Current - Output (Max) 1.05A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Topology	AC DC Converter	
Voltage - Input (Max) 528VAC Voltage - Output 71 ~ 142 V Current - Output (Max) 1.05A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Number of Outputs	1	
Voltage - Output 71 ~ 142 V Current - Output (Max) 1.05A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Voltage - Input (Min)	249VAC	
Current - Output (Max) Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Size / Dimension 1.05A 1.05A 1.05W 1.05W 3.75kV (3750V) 3.75kV (3750V) 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.0000 4.00	Voltage - Input (Max)	528VAC	
Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Wire Leads Size / Dimension 150W 3.75kV (3750V) Analog Features OTP, OVP, SCP 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Voltage - Output	71 ~ 142 V	
Voltage - Isolation 3.75kV (3750V) Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Size / Dimension 3.75kV (3750V) Analog OTP, OVP, SCP WY X 1.71" H (220.0mm x 93.9mm x 43.5mm)	Current - Output (Max)	1.05A	
Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Power (Watts)	150W	
Features OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Voltage - Isolation	3.75kV (3750V)	
Ratings IP67 Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Dimming	Analog	
Operating Temperature -35°C ~ 65°C Efficiency 90% Termination Style Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Features	OTP, OVP, SCP	
Efficiency 90% Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Ratings	IP67	
Termination Style Wire Leads Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Operating Temperature	-35°C ~ 65°C	
Size / Dimension 8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	Efficiency	90%	
	Termination Style	Wire Leads	
Report errors?	Size / Dimension	8.66" L x 3.70" W x 1.71" H (220.0mm x 93.9mm x 43.5mm)	
			Report errors?

LXD150-1050SH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LXD150-1050SH Payment Methods





















LXD150-1050SH Shipping Methods













If you have any question about LXD150-1050SH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com