



LXD40-0700SW Information

Heisener.com

Part Number LXD40-0700SW

Manufacturer Excelsys Technologies Ltd

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CC AC/DC 18-54V 700MA

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LXD40-0700SW Specifications

Manufacturer Part Number LXD40-0700SW Manufacturer Excelsys Technologies Ltd Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LXD40 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 18 ~ 54 V Current - Output (Max) 700mA Power (Watts) 40W Voltage - Isolation 3kV (3000V) Dimming Analog Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)			
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LXD40 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 18 ~ 54 V Current - Output (Max) 700mA Power (Watts) 40W Voltage - Isolation 3kV (3000V) Dimming Analog Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Manufacturer Part Number	LXD40-0700SW	
LED Drivers Package - Series LXD40 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 18 ~ 54 V Current - Output (Max) 700mA Power (Watts) 40W Voltage - Isolation 3kV (3000V) Dimming Analog Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Manufacturer	Excelsys Technologies Ltd	
Package - Series LXD40 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 18 ~ 54 V Current - Output (Max) 700mA Power (Watts) 40W Voltage - Isolation 3kV (3000V) Dimming Analog Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series LXD40 Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 18 ~ 54 V Current - Output (Max) 700mA Power (Watts) 40W Voltage - Isolation 3kV (3000V) Dimming Analog Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)		LED Drivers	
Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 18 ~ 54 V Current - Output (Max) 700mA Power (Watts) 40W Voltage - Isolation 3kV (3000V) Dimming Analog Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Package	-	
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 18 ~ 54 V Current - Output (Max) 700mA Power (Watts) 40W Voltage - Isolation 3kV (3000V) Dimming Analog Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Series	LXD40	
Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 18 ~ 54 V Current - Output (Max) 700mA Power (Watts) 40W Voltage - Isolation 3kV (3000V) Dimming Analog Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Туре	Constant Current	
Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 18 ~ 54 V Current - Output (Max) 700mA Power (Watts) 40W Voltage - Isolation 3kV (3000V) Dimming Analog Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Topology	AC DC Converter	
Voltage - Input (Max) 305VAC Voltage - Output 18 ~ 54 V Current - Output (Max) 700mA Power (Watts) 40W Voltage - Isolation 3kV (3000V) Dimming Analog Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Number of Outputs	1	
Voltage - Output 18 ~ 54 V Current - Output (Max) 700mA Power (Watts) 40W Voltage - Isolation 3kV (3000V) Dimming Analog Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Voltage - Input (Min)	90VAC	
Current - Output (Max) 700mA Power (Watts) 40W Voltage - Isolation 3kV (3000V) Dimming Analog Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Voltage - Input (Max)	305VAC	
Power (Watts) 40W Voltage - Isolation 3kV (3000V) Dimming Analog Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Voltage - Output	18 ~ 54 V	
Voltage - Isolation 3kV (3000V) Dimming Analog Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Current - Output (Max)	700mA	
DimmingAnalogFeaturesOVP, SCPRatingsIP66Operating Temperature-20°C ~ 60°CEfficiency87%Termination StyleWire LeadsSize / Dimension3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Power (Watts)	40W	
Features OVP, SCP Ratings IP66 Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Voltage - Isolation	3kV (3000V)	
Ratings IP66 Operating Temperature $-20^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74° L x 2.76° W x 1.26° H (95.0mm x 70.0 mm x 32.0 mm)	Dimming	Analog	
Operating Temperature -20°C ~ 60°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Features	OVP, SCP	
Efficiency 87% Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Ratings	IP66	
Termination Style Wire Leads Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Operating Temperature	-20°C ~ 60°C	
Size / Dimension 3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	Efficiency	87%	
	Termination Style	Wire Leads	
Report errors?	Size / Dimension	3.74" L x 2.76" W x 1.26" H (95.0mm x 70.0mm x 32.0mm)	
			Report errors?

LXD40-0700SW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LXD40-0700SW Payment Methods

































If you have any question about LXD40-0700SW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com