

LXV100-081S Information



For Reference Only

Part Number LXV100-081S

Manufacturer Excelsys Technologies Ltd

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CV AC/DC 81V 1.23A

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









	0040	~	
LXV100-	·081S S	Specification	S

Manufacturer Part Number LXV100-081S Manufacturer Excelsys Technologies Ltd Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LXV100 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output (Max) 1.23A Current - Output (Max) 1.23A Power (Watts) 100W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	•		
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LXV100 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Output (Max) 264VAC Voltage - Output (Max) 1.23A Power (Watts) 100W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Manufacturer Part Number	LXV100-081S	
Package - Series LXV100 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 81V Current - Output (Max) 1.23A Power (Watts) 100W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Manufacturer	Excelsys Technologies Ltd	
Package - Series LXV100 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 81V Current - Output (Max) 1.23A Power (Watts) 100W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series LXV100 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 81V Current - Output (Max) 1.23A Power (Watts) 100W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)		LED Drivers	
Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 81V Current - Output (Max) 1.23A Power (Watts) 100W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Package	-	
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 81V Current - Output (Max) 1.23A Power (Watts) 100W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Series	LXV100	
Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 81V Current - Output (Max) 1.23A Power (Watts) 100W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Туре	Constant Voltage	
Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 81V Current - Output (Max) 1.23A Power (Watts) 100W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Topology	AC DC Converter	
Voltage - Input (Max) 264VAC Voltage - Output 81V Current - Output (Max) 1.23A Power (Watts) 100W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Number of Outputs	1	
Voltage - Output 81V Current - Output (Max) 1.23A Power (Watts) 100W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Voltage - Input (Min)	90VAC	
Current - Output (Max) Power (Watts) 100W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 1.23A 1.00W 3.75kV (3750V) 0.00C 3.75kV (3750V) 0.00C 0.	Voltage - Input (Max)	264VAC	
Power (Watts) 100W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Voltage - Output	81V	
Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Current - Output (Max)	1.23A	
Dimming Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Power (Watts)	100W	
Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Voltage - Isolation	3.75kV (3750V)	
Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Dimming	-	
Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Features	OCP, OTP, OVP, SCP	
Efficiency 93% Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Ratings	IP67	
Termination Style Wire Leads Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Operating Temperature	-35°C ~ 70°C	
Size / Dimension 7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	Efficiency	93%	
	Termination Style	Wire Leads	
Report errors?	Size / Dimension	7.24" L x 2.66" W x 1.46" H (184.0mm x 67.5mm x 37.0mm)	
		Report errors?	

LXV100-081S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LXV100-081S Payment Methods



















LXV100-081S Shipping Methods













If you have any question about LXV100-081S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com