

LXV200-054S Information

WWW Pro Dom

For Reference Only

Part Number LXV200-054S

Manufacturer Excelsys Technologies Ltd

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CV AC/DC 54V 3.7A

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LXV200-054S Specifications

Manufacturer Part Number LXV200-054S Manufacturer Excelsys Technologies Ltd Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LXV200 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 54V Current - Output (Max) 3.7A Power (Watts) 200W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	-	
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LXV200 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 54V Current - Output (Max) 3.7A Power (Watts) 200W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Manufacturer Part Number	LXV200-054S
Package - Series LXV200 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 54V Current - Output (Max) 3.7A Power (Watts) 200W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Manufacturer	Excelsys Technologies Ltd
Package - Series LXV200 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Output (Max) 264VAC Voltage - Output (Max) 3.7A Power (Watts) 200W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series LXV200 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 54V Current - Output (Max) 3.7A Power (Watts) 200W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)		LED Drivers
Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 54V Current - Output (Max) 3.7A Power (Watts) 200W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Package	-
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 54V Current - Output (Max) 3.7A Power (Watts) 200W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Series	LXV200
Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 54V Current - Output (Max) 3.7A Power (Watts) 200W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Type	Constant Voltage
Voltage - Input (Min) 90VAC Voltage - Input (Max) 264VAC Voltage - Output 54V Current - Output (Max) 3.7A Power (Watts) 200W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Topology	AC DC Converter
Voltage - Input (Max) 264VAC Voltage - Output 54V Current - Output (Max) 3.7A Power (Watts) 200W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Number of Outputs	1
Voltage - Output 54V Current - Output (Max) 3.7A Power (Watts) 200W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Voltage - Input (Min)	90VAC
Current - Output (Max) 3.7A Power (Watts) 200W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Voltage - Input (Max)	264VAC
Power (Watts) 200W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Voltage - Output	54V
Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Current - Output (Max)	3.7A
Dimming Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Power (Watts)	200W
Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Voltage - Isolation	3.75kV (3750V)
RatingsIP67Operating Temperature $-35^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Efficiency 93% Termination StyleWire LeadsSize / Dimension $7.84^{\circ}\text{L} \times 2.66^{\circ} \text{W} \times 1.58^{\circ} \text{H} (199.0 \text{mm} \times 67.5 \text{mm} \times 40.0 \text{mm})$	Dimming	-
Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Features	OCP, OTP, OVP, SCP
Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Ratings	IP67
Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Operating Temperature	-35°C ~ 70°C
Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Efficiency	93%
	Termination Style	Wire Leads
Report errors?	Size / Dimension	7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)
		Report errors?

LXV200-054S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LXV200-054S Payment Methods



















LXV200-054S Shipping Methods













If you have any question about LXV200-054S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com