

LY1-DC24 Information

www.com

For Reference Only

Part Number LY1-DC24

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 15A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LY1-DC24 Specifications

Manufacturer Part Number LY1-DC24 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series LY Relay Type General Purpose Coil Type Non Latching Coil Current 36.9mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In		
Category Relays Power Relays, Over 2 Amps Package - Series LY Relay Type General Purpose Coil Type Non Latching Coil Current 36.9mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Manufacturer Part Number	LY1-DC24
Package-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.9mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)15ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package - Series LY Relay Type General Purpose Coil Type Non Latching Coil Current 36.9mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.9mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)15ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 36.9mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current36.9mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)15ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	LY
Coil Current36.9mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)15ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Release Time - 25ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Release Time 5 cocketable Termination Style Plug In	Coil Current	36.9mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style	Coil Voltage	24VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style 19.2 VDC 2.4 VDC 2.5 MDC 2.5 MDC	Contact Rating (Current)	15A
Turn Off Voltage (Min) Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	19.2 VDC
Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	2.4 VDC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	25ms
Mounting Type Socketable Termination Style Plug In	Release Time	25ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

LY1-DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LY1-DC24 Payment Methods



















LY1-DC24 Shipping Methods













If you have any question about LY1-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com