

LY2-AC24 Information



For Reference Only

Part Number LY2-AC24

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 10A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LY2-AC24 Specifications

Manufacturer LY2-AC24 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series LY Relay Type General Purpose Coil Type Non Latching Coil Current 46mA Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In		
Category Relays Power Relays, Over 2 Amps Package - Series LY Relay Type General Purpose Coil Type Non Latching Coil Current 46mA Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Manufacturer Part Number	LY2-AC24
Package-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46mACoil Voltage24VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package - Series LY Relay Type General Purpose Coil Type Non Latching Coil Current 46mA Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46mACoil Voltage24VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 46mA Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 25ms Release Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current46mACoil Voltage24VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	LY
Coil Current 46mA Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 25ms Release Time 25ms Features Mounting Type Socketable Termination Style Plug In	Relay Type	General Purpose
Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 25ms Release Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Coil Current	46mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style	Coil Voltage	24VAC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style 19.2 VAC 7.2 VAC Plug In	Contact Rating (Current)	10A
Turn Off Voltage (Min) 7.2 VAC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	19.2 VAC
Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	7.2 VAC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	25ms
Mounting Type Socketable Termination Style Plug In	Release Time	25ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

LY2-AC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LY2-AC24 Payment Methods



















LY2-AC24 Shipping Methods













If you have any question about LY2-AC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com