

# LY2-D-DC12

uest a Quote

## LY2-D-DC12 Information

www.ecom	Part Number	LY2-D-DC12	
	Manufacturer	Omron Automation and Safety	
	Category	Relays Power Relays, Over 2 Amps	- RS
	Description	RELAY GEN PURPOSE DPDT 10A 12V	- 32'
	Package	-	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Req

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## LY2-D-DC12 Specifications

Manufacturer Part NumberLY2-D-DC12ManufacturerOmron Automation and SafetyCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Qurrent75mAContact FormDPDT (2 Form C)Contact Rating (Current)JOVAC, 125VDC - MaxSwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCOperate TimeSinsRelease TimeSocketableFeaturesDiodeMounting TypePug InPug ManufacturesPug InHounting TypePug In		
CategoryRelaysPower Relays, Over 2 AmpsPackagePackageSeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage (Max)9.6 VDCTurn On Voltage (Max)9.6 VDCOperate Time25msRelease TimeDiodeFeaturesDiodeMounting TypeSocketablePurn In StylePurp In	Manufacturer Part Number	LY2-D-DC12
PackagePower Relays, Over 2 AmpsPackage-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage (Max)9.6 VDCTurn On Voltage (Max)1.2 VDCOperate Time25msRelease Time25msFeaturesDiodeMounting TypeSocketableTermination StylePug In	Manufacturer	Omron Automation and Safety
Package-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time25msRelease TimeDiodeFeaturesDiodeMounting TypeSocketableTermination StylePug In	Category	Relays
SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage9.6 VDC - MaxTurn On Voltage (Max)9.6 VDCOperate Time25msRelease Time25msFeaturesDiodeMounting TypeSocketablePurp InternetPing InternetPurp InternetPing Internet		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage9.6 VDC - MaxTurn On Voltage (Max)9.6 VDCOperate Time25msRelease Time25msFeaturesDiodeMounting TypeSoketablePurpose<	Package	-
Coil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time25msRelease Time25msFeaturesDiodeMounting TypeSocketablePurg InPurg In	Series	LY
Coil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time25msRelease Time25msFeaturesDiodeMounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time25msRelease Time25msFeaturesDiodeMounting TypeSocketablePremination StylePlug In	Coil Type	Non Latching
Contact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time25msRelease Time25msFeaturesDiodeMounting TypeSocketableTermination StylePlug In	Coil Current	75mA
Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time25msRelease Time25msFeaturesDiodeMounting TypeSocketableTermination StylePlug In	Coil Voltage	12VDC
Switching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time25msRelease Time25msFeaturesDiodeMounting TypeSocketableTermination StylePlug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time25msRelease Time25msFeaturesDiodeMounting TypeSocketableTermination StylePlug In	Contact Rating (Current)	10A
Turn Off Voltage (Min)1.2 VDCOperate Time25msRelease Time25msFeaturesDiodeMounting TypeSocketableTermination StylePlug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time25msRelease Time25msFeaturesDiodeMounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	9.6 VDC
Release Time25msFeaturesDiodeMounting TypeSocketableTermination StylePlug In	Turn Off Voltage (Min)	1.2 VDC
FeaturesDiodeMounting TypeSocketableTermination StylePlug In	Operate Time	25ms
Mounting TypeSocketableTermination StylePlug In	Release Time	25ms
Termination Style Plug In	Features	Diode
	Mounting Type	Socketable
	Termination Style	Plug In
Report error		Report errors?

### LY2-D-DC12 Guarantees



#### Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# LY2-D-DC12 Payment Methods



# LY2-D-DC12 Shipping Methods



If you have any question about LY2-D-DC12, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com