



### LY2-T130 DC24 Information

Heisener.com

Part Number LY2-T130 DC24

Manufacturer Omron Automation and Safety

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 10A 24V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com

Request a Quote



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **LY2-T130 DC24 Specifications**

Manufacturer Part NumberLY2-T130 DC24ManufacturerOmron Automation and SafetyCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	LY2-T130 DC24
Package-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package         -           Series         LY           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         36.9mA           Coil Voltage         24VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         10A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         19.2 VDC           Turn Off Voltage (Min)         2.4 VDC           Operate Time         25ms           Release Time         25ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 36.9mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current36.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	LY
Coil Current36.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Release Time - Contact Rating (Current) 25ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  25ms  Release Time  25ms  Release Time  5 cocketable  Termination Style  Plug In	Coil Current	36.9mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  25ms  Release Time  25ms  Features  -  Mounting Type  Socketable  Termination Style	Coil Voltage	24VDC
Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 25ms  Release Time 25ms  Features -  Mounting Type Socketable  Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  25ms  Release Time  25ms  Features  - Mounting Type  Socketable  Termination Style  19.2 VDC  2.4 VDC  2.5 MDC  2.5 MDC	Contact Rating (Current)	10A
Turn Off Voltage (Min)  Operate Time  25ms  Release Time  25ms  Features  - Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 25ms  Release Time 25ms  Features -  Mounting Type Socketable  Termination Style Plug In	Turn On Voltage (Max)	19.2 VDC
Release Time 25ms  Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	2.4 VDC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	25ms
Mounting Type Socketable Termination Style Plug In	Release Time	25ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

#### LY2-T130 DC24 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **LY2-T130 DC24 Payment Methods**





















## LY2-T130 DC24 Shipping Methods













If you have any question about LY2-T130 DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com