



LY2N-D2 DC48 Information



For Reference Only

Part Number LY2N-D2 DC48

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 10A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LY2N-D2 DC48 Specifications

Manufacturer Part NumberLY2N-D2 DC48ManufacturerOmron Automation and SafetyCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.5mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		
Category Relays Power Relays, Over 2 Amps Package - Series LY Relay Type General Purpose Coil Type Non Latching Coil Current 18.5mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Manufacturer Part Number	LY2N-D2 DC48
Package-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.5mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package - Series LY Relay Type General Purpose Coil Type Non Latching Coil Current 18.5mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.5mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 18.5mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current18.5mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Series	LY
Coil Current Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 25ms Release Time LED Indicator Mounting Type Socketable Termination Style	Coil Current	18.5mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 25ms Release Time LED Indicator Mounting Type Socketable Termination Style	Coil Voltage	48VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 25ms Release Time 25ms LED Indicator Mounting Type Socketable Termination Style 38.4 VDC 4.8 VDC LED Indicator Description: Socketable Plug In	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 25ms Release Time 25ms LED Indicator Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	38.4 VDC
Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	4.8 VDC
Features LED Indicator Mounting Type Socketable Termination Style Plug In	Operate Time	25ms
Mounting Type Socketable Termination Style Plug In	Release Time	25ms
Termination Style Plug In	Features	LED Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

LY2N-D2 DC48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LY2N-D2 DC48 Payment Methods



















LY2N-D2 DC48 Shipping Methods













If you have any question about LY2N-D2 DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com