



LY2ZN DC100/110 Information



For Reference Only

Part Number LY2ZN DC100/110

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 110V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LY2ZN DC100/110 Specifications

Manufacturer Part Number LY2ZN DC100/110 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series LY Relay Type General Purpose Coil Type Non Latching Coil Current 10mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In		
Category Relays Power Relays, Over 2 Amps Package	Manufacturer Part Number	LY2ZN DC100/110
Package-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)11 VDCOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)11 VDCOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)11 VDCOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 10mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 25ms Release Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current10mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)11 VDCOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Series	LY
Coil Current10mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)11 VDCOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 25ms Release Time 25ms Release Time LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 25ms Release Time 25ms Release Time LED Indicator Mounting Type Socketable Termination Style	Coil Current	10mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style	Coil Voltage	110VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 25ms Release Time 25ms LED Indicator Mounting Type Socketable Termination Style 88 VDC LED Indicator 88 VDC LED Indicator	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	88 VDC
Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	11 VDC
Features LED Indicator Mounting Type Socketable Termination Style Plug In	Operate Time	25ms
Mounting Type Socketable Termination Style Plug In	Release Time	25ms
Termination Style Plug In	Features	LED Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

LY2ZN DC100/110 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LY2ZN DC100/110 Payment Methods



















LY2ZN DC100/110 Shipping Methods













If you have any question about LY2ZN DC100/110, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com