



### LY3I4-AC100/110 Information

www.isener.com

For Reference Only

Part Number LY3I4-AC100/110

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 3PDT 10A 110V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# LY3I4-AC100/110 Specifications

| Manufacturer Part Number         LY314-AC100/110           Manufacturer         Omron Automation and Safety           Category         Relays           Package         -           Series         LY           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         15.6mA           Coil Voltage         110VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         10A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         88 VAC           Turn Off Voltage (Min)         33 VAC           Operate Time         25ms           Release Time         25ms           Features         Test Button           Mounting Type         Socketable           Termination Style         Plug In |                          |                             |
|---|--------------------------|-----------------------------|
| Category Relays Power Relays, Over 2 Amps Package Power Relays, Over 2 Amps  LY Relay Type General Purpose Coil Type Non Latching Coil Current 15.6mA Coil Voltage 110VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 25ms Release Time 25ms Features Test Button Mounting Type Socketable Termination Style   | Manufacturer Part Number | LY3I4-AC100/110             |
| Package-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15.6mACoil Voltage110VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time25msRelease Time25msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In  | Manufacturer             | Omron Automation and Safety |
| Package         -           Series         LY           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         15.6mA           Coil Voltage         110VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         10A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         88 VAC           Turn Off Voltage (Min)         33 VAC           Operate Time         25ms           Release Time         25ms           Features         Test Button           Mounting Type         Socketable           Termination Style         Plug In   | Category                 | Relays                      |
| SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15.6mACoil Voltage110VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time25msRelease Time25msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In  |                          | Power Relays, Over 2 Amps   |
| Relay Type General Purpose Coil Type Non Latching Coil Current 15.6mA Coil Voltage 110VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 25ms Release Time 25ms Release Time 25ms Features Test Button Mounting Type Socketable Termination Style Plug In   | Package                  | -                           |
| Coil TypeNon LatchingCoil Current15.6mACoil Voltage110VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time25msRelease Time25msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In   | Series                   | LY                          |
| Coil Current15.6mACoil Voltage110VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time25msRelease Time25msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In  | Relay Type               | General Purpose             |
| Coil Voltage 110VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 25ms Release Time 25ms Features Test Button Mounting Type Socketable Termination Style Plug In   | Coil Type                | Non Latching                |
| Contact Form 3PDT (3 Form C)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 88 VAC  Turn Off Voltage (Min) 33 VAC  Operate Time 25ms  Release Time 25ms  Release Time 25ms  Features Test Button  Mounting Type Socketable  Termination Style Plug In   | Coil Current             | 15.6mA                      |
| Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  88 VAC  Turn Off Voltage (Min)  33 VAC  Operate Time  25ms  Release Time  25ms  Features  Test Button  Mounting Type  Socketable  Termination Style   | Coil Voltage             | 110VAC                      |
| Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 88 VAC  Turn Off Voltage (Min) 33 VAC  Operate Time 25ms  Release Time 25ms  Features Test Button  Mounting Type Socketable  Termination Style Plug In  | Contact Form             | 3PDT (3 Form C)             |
| Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  25ms  Release Time  25ms  Features  Test Button  Mounting Type  Socketable  Termination Style  Plug In   | Contact Rating (Current) | 10A                         |
| Turn Off Voltage (Min)  Operate Time  25ms  Release Time  25ms  Features  Test Button  Mounting Type  Socketable  Termination Style  Plug In  | Switching Voltage        | 250VAC, 125VDC - Max        |
| Operate Time25msRelease Time25msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In  | Turn On Voltage (Max)    | 88 VAC                      |
| Release Time 25ms Features Test Button Mounting Type Socketable Termination Style Plug In   | Turn Off Voltage (Min)   | 33 VAC                      |
| Features Test Button  Mounting Type Socketable  Termination Style Plug In   | Operate Time             | 25ms                        |
| Mounting Type Socketable Termination Style Plug In  | Release Time             | 25ms                        |
| Termination Style Plug In   | Features                 | Test Button                 |
|   | Mounting Type            | Socketable                  |
| Report errors?  | Termination Style        | Plug In                     |
|   |                          | Report errors?              |

#### LY3I4-AC100/110 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### LY3I4-AC100/110 Payment Methods



















# LY3I4-AC100/110 Shipping Methods













If you have any question about LY3I4-AC100/110, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com