



### LY3N AC110/120 Information

Part Number LY3N AC110/120

Manufacturer Omron Automation and Safety

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 3PDT 10A 120V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# LY3N AC110/120 Specifications

Manufacturer Part Number         LY3N AC110/120           Manufacturer         Omron Automation and Safety           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         LY           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         14.8mA           Coil Voltage         120VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         10A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         96 VAC           Turn Off Voltage (Min)         36 VAC           Operate Time         25ms           Release Time         25ms           Features         LED Indicator           Mounting Type         Socketable           Termination Style         Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current14.8mACoil Voltage120VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	LY3N AC110/120
Package-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current14.8mACoil Voltage120VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package         -           Series         LY           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         14.8mA           Coil Voltage         120VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         10A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         96 VAC           Turn Off Voltage (Min)         36 VAC           Operate Time         25ms           Release Time         25ms           Features         LED Indicator           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current14.8mACoil Voltage120VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 14.8mA Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 25ms Release Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current14.8mACoil Voltage120VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Series	LY
Coil Current Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 120VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 25ms Release Time 25ms Release Time LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form 3PDT (3 Form C)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 96 VAC  Turn Off Voltage (Min) 36 VAC  Operate Time 25ms  Release Time 25ms  Release Time LED Indicator  Mounting Type Socketable  Termination Style Plug In	Coil Current	14.8mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  96 VAC  Turn Off Voltage (Min)  36 VAC  Operate Time  25ms  Release Time  25ms  Features  LED Indicator  Mounting Type  Socketable  Termination Style	Coil Voltage	120VAC
Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 96 VAC  Turn Off Voltage (Min) 36 VAC  Operate Time 25ms  Release Time 25ms  Features LED Indicator  Mounting Type Socketable  Termination Style Plug In	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max)  7 Turn Off Voltage (Min)  96 VAC  Operate Time  25 ms  Release Time  25 ms  LED Indicator  Mounting Type  Socketable  Termination Style  Plug In	Contact Rating (Current)	10A
Turn Off Voltage (Min)  Operate Time  25ms  Release Time  25ms  Features  LED Indicator  Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 25ms  Release Time 25ms  Features LED Indicator  Mounting Type Socketable  Termination Style Plug In	Turn On Voltage (Max)	96 VAC
Release Time 25ms  Features LED Indicator  Mounting Type Socketable  Termination Style Plug In	Turn Off Voltage (Min)	36 VAC
Features LED Indicator  Mounting Type Socketable  Termination Style Plug In	Operate Time	25ms
Mounting Type Socketable Termination Style Plug In	Release Time	25ms
Termination Style Plug In	Features	LED Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

#### LY3N AC110/120 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### LY3N AC110/120 Payment Methods



















# LY3N AC110/120 Shipping Methods













If you have any question about LY3N AC110/120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com